

Accessories

Accessories for industrial vacuum solutions



Accessories for industrial vacuums

Using the right accessory makes easier and efficient your daily work enhancing the performance of your Nilfisk industrial vacuum.

This catalogue allows you to identify the most suitable accessories for all vacuum cleaners and applications. In the tables, you will find the main features of the different accessories, an indication of the sectors where they are recommended to be used and if they are ATEX certified.

A short description of the food, pharma and ATEX range:

· Accessories for the food sector:

The color-coded program is one of the main requests of the food sector: each color is matched to a specific production area, in order to avoid any cross contamination or bacteria migration inside the plant. Nilfisk provides a selection of 6 colors of FDA approved accessories for any application. Moreover, a specific range for high temperatures is available, in order to meet any need in ovens cleaning and high temperature material collection, keeping the product quality at the top.

· Accessories for the pharmaceutical sector:

Nilfisk accessories for pharmaceutical applications are designed to meet any possible need in terms of safety, hygiene and efficiency. Accessories quality is at the top: FDA certified, the metal parts are made in stainless steel AISI 316L, they can be sterilized placing them in autoclave.


· Accessories for vacuum cleaners in ATEX zones

The range of ATEX accessories suitable for II 2D 2G has been developed in order to increase the safety of our industrial vacuums.



How to use the new and certified sequence of ATEX accessories

The ATEX sequence of accessories starts from the inlet which features a hole where to mount the first accessory with a pushbutton. The whole sequence of accessories can be then connected by using male and female parts, along the complete sequence, from the inlet to the final tool. Only accessories with these metal parts will be marked as certified. Here below the marking that all Nilfisk ATEX accessories will feature:




Please feel free to contact us at any time for more details or for the latest information.

+39 059 9730000

industrial-vacuum@nilfisk.com

Standard VS ATEX accessories



KEY TO ICONS:



METAL



PHARMA/
CHEMICAL



HEAVY
INDUSTRY



ATEX



FOOD



BUILDING &
CONSTRUCTION



GENERAL
CLEANING

Table of contents


ACCESSORIES FOR INDUSTRIAL VACUUMS	2	4 HANDGRIPS AND EXTENSIONS	
STANDARD VS ATEX ACCESSORIES.....	3	4.a Handgrips	42
		4.b Examples	45
1 CONNECTION DIAGRAMS		5 FLOOR NOZZLES AND BRUSHES	
1.a Nilfisk Vacuum cleaner	4	5.a Floor nozzles	48
1.b Nilfisk ATEX Vacuum cleaner	6	5.b Brushes.....	54
		5.c Examples.....	57
2 HOSES AND SLEEVES		6 FINAL TOOLS	
2.a Hoses.....	8	6.a Rubber tools	60
2.b Sleeves.....	24	6.b Examples	74
3 HOSE CONNECTORS AND REDUCTIONS		7 ACCESSORIES KIT	80
3.a Hose connectors	26		
3.b Reductions.....	31		
3.c Examples.....	38		


Connection Diagrams

1.a Nilfisk Vacuum Cleaner

How to connect **Nilfisk** accessories to **Nilfisk** vacuum cleaners.

- | | |
|---|---|
| A See chapter 3
Hose connectors and
Reductions | G See chapter 6.a
Crevice nozzles |
| B See chapter 2.b
Sleeves | H See chapter 5.b
Round brushes |
| C See chapter 2.a
Hoses | I See chapter 6
Final tools |
| D See chapter 4.a
Extensions | J See chapter 5.b
Brushes |
| E See chapter 3.a
Curved connectors | K See chapter 5.a
Nozzles |
| F See chapter 4.a
Handgrips | |







1.b Nilfisk ATEX Vacuum Cleaner

How to connect accessories on an **ATEX** industrial vacuum.

- | | |
|---|---|
| A See chapter 7
Inlet | G See chapter 4.a
Handgrips |
| B See chapter 2.a
Hoses | H See chapter 6.a
Crevice nozzles |
| C See chapter 3.b
Reductions | I See chapter 5.b
Brushes |
| D See chapter 3.b
Bifurcations | J See chapter 6
Final tools |
| E See chapter 4.a
Extensions | K See chapter 5.a
Floor nozzles |
| F See chapter 3.a
Curved Connectors | |





Hoses and Sleeves

This chapter contains tables with the descriptions of the various types of hoses, divided by application, and indications of the sleeves to choose based on the hose used.

The last part of the chapter contains useful examples of the connections between hoses and sleeves.

2.a Hoses

FLEX HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	In EVA (ethyl-vinyl-acetate) spiralled and unreinforced + PVC sleeves	included (Z7 23022)					•	•							•	Z7 22150			
		5							•	•							•	Z7 22360			
		15							•	•							•	4072200469			
		30		not included (P/N to order: Z7 23022)					•	•							•	4072400231			
	50	3		included (Z7 23023)					•	•									•	Z7 22151	
		5							•	•									•	Z7 22361	
		15							•	•									•	4072200470	
		30 complete roll		not included (P/N to order: Z7 23023)					•	•									•	4072400232	
The Flex Hose is suitable for cleaning dust and non-abrasive materials. It is a light and flexible grey hose, corrugated both externally and on the inside. Range of temperature: -30° C +60° C.																					

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

AIR HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	30	by meter	Plastified PVC hose with rigid PVC spiral + rubber sleeves	N/A					•	•				•	•	•			•	Z8 24023	
	40	3		included (Z7 20001)					•	•				•	•	•			•	Z7 22049	
		5							•	•			•	•	•			•	Z7 22362		
		10							•	•			•	•	•			•	4072200504		
		15							•	•			•	•	•			•	4072200471		
		50 complete roll			not included (P/N to order: Z7 20001)					•	•			•	•	•			•	4072400227	
	50	3		included (Z7 20002)					•	•				•	•	•			•	Z7 22062	
		5							•	•			•	•	•			•	Z7 22363		
		10							•	•			•	•	•			•	4072200505		
		15							•	•			•	•	•			•	4072200472		
		50 complete roll		not included (P/N to order: Z7 20002)					•	•			•	•	•			•	4072400228		
	70	3		included (Z7 20003)					•	•				•	•	•			•	Z7 22063	
		5							•	•			•	•	•			•	Z7 22364		
		10							•	•			•	•	•			•	4072200506		
		15							•	•			•	•	•			•	4072200473		
		50 complete roll		not included (P/N to order: Z7 20003)					•	•			•	•	•			•	4072400229		
	100	by meter		not included (P/N to order 4072000362)					•	•				•	•	•			•	Z7 24027	
		30 complete roll							•	•			•	•	•			•	4072400230		
The Air Hose is ideal for cleaning dust and non-abrasive materials. It is a light, flexible, grey hose. It is corrugated externally and smooth on the inside. Range of temperature: -10° C +60° C.																					

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

FLEX CONDUCTIVE HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								CERTIFIED THIRD PARTY APPROVAL	SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE											
	38/40	3	Spiral conductive PE hose with reinforcement on the external spiral with antiabrasion function + conductive polyurethane sleeves	4072000343		•			•	•					•			•	•	4072200509		
		5		4072000343		•			•	•					•			•	•	4072200510		
		15		4072000343		•			•	•					•			•	•	4072200480		
		30 complete roll		not included (P/N to be ordered 4072000343)		•			•	•					•			•	•	4072400233		
	50	3		Z7 20325		•			•	•					•			•	•	Z7 22375		
		5		Z7 20325		•			•	•					•			•	•	Z7 22377		
		15		Z7 20325		•			•	•					•			•	•	4072200481		
		30 complete roll		not included (P/N to be ordered Z7 20325)		•			•	•					•			•	•	4072400234		
	70	3		4072000348		•			•	•					•			•	•	4072200542		
		5		4072000348		•			•	•					•			•	•	4072200543		
The Flex hose is a conductive hose made of polyethylene and ethyl-vinyl-acetate (EVA). It is suitable for cleaning dust, non-abrasive materials, and conductive materials. It is black, with a grey line on the ridge; it is flexible and is corrugated externally and smooth on the inside. Range of temperature: -20° / + 60°C																						

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

CONDUCTIVE POLYURETHANE HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE		
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	3	PU conductive flexible, spiral tube with copper-plated steel armor covered in conductive PU + conductive polyurethane sleeves	40000212	•	•								•			•	•		•	Z7 22368		
		5		40000212	•	•								•			•	•		•	Z7 22371		
		10		40000212	•	•								•			•	•		•	Z7 22351		
		15		40000212	•	•								•			•	•		•	4072200477		
	50	3		40000219	•	•									•			•	•		•	Z7 22369	
		5		40000219	•	•									•			•	•		•	Z7 22372	
		10		40000219	•	•									•			•	•		•	Z7 22352	
		15		40000219	•	•									•			•	•		•	4072200478	
	70	3		Z7 20310	•	•										•			•	•		•	Z7 22370
		5		Z7 20310	•	•										•			•	•		•	Z7 22373
		15		Z7 20310	•	•										•			•	•		•	4072200479
	100	by meter		not included (P/N to order Z8 40044 - metal tie)	•	•										•			•	•		•	4072400259
The conductive polyurethane hose can be used for cleaning abrasive materials, conductive materials, and liquids. It is black, highly flexible and is corrugated externally and smooth on the inside. Range of temperature: -30° / + 90°C.																							

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

CONDUCTIVE POLYURETHANE EXA HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	Conductive polyurethane hose + Stainless Steel AISI 304 hose connectors	Male and female connectors + heat shrink sleeve	•	•						•	•			•	•		4072400489		
		5			•	•						•	•			•	•		4072400490		
		10			•	•						•	•			•	•		4072400491		
		15			•	•						•	•			•	•		4072400492		
	50	3			•	•						•	•			•	•		4072400493		
		5			•	•						•	•			•	•		4072400494		
		10			•	•						•	•			•	•		4072400495		
		15			•	•						•	•			•	•		4072400496		
	70	3			•	•						•	•			•	•		4072400497		
		5			•	•						•	•			•	•		4072400498		
		10			•	•						•	•			•	•		4072400499		
		15			•	•						•	•			•	•		4072400500		
	100	3			•	•						•	•			•	•		4072400501		
		5			•	•						•	•			•	•		4072400502		
		10			•	•						•	•			•	•		4072400503		
		15			•	•						•	•			•	•		4072400504		
The conductive polyurethane hose can be used for cleaning abrasive materials, conductive materials, and liquids. It is black, highly flexible and is corrugated externally and smooth on the inside. It is connected with two metal connectors through a rivet and covered by a black heat shrink cover. Metal connectors will be marked according to the type of hose. Range of temperature: -30° / + 90°C.																					

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

RUBBER HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	Smooth black conductive rubber, abrasion resistant	Integrated sleeves	•	•		•						•			•	•		•	Z7 24005
		5			•	•		•					•			•	•		•	Z7 24178	
	50	3			•	•		•					•			•	•		•	Z7 24003	
		5			•	•		•					•			•	•		•	Z7 24179	
	70	3			•	•		•					•			•	•		•	Z7 24001	
		5			•	•		•					•			•	•		•	Z7 24180	
	50	5			•	•		•					•			•	•		•	ZA7240005	
		10			•	•		•					•			•	•		•	ZA7240003	
	70	5			•	•		•					•			•	•		•	ZA7240015	
		10			•	•		•					•			•	•		•	ZA7240018	
	100	5			•	•		•					•			•	•		•	ZA7240011	
		10			•	•		•					•			•	•		•	ZA7240042	
The rubber oilproof hose is suitable for cleaning metal shavings mixed with traces of oil, dust and conductive materials. It is corrugated externally and smooth on the inside. It has a metal wire to earth the hose. Temperature range - 40° / + 120°C.																					

RUBBER EXA HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE		
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	3	Conductive rubber hose + Stainless Steel AISI 304 hose connectors	Male and female connectors + heat shrink sleeve	•	•		•				•	•			•	•		• for EXA machines	4072400483			
		5			•	•		•				•	•			•	•			4072400484			
	50	3			•	•		•				•	•			•	•			4072400485			
		5			•	•		•				•	•			•	•			4072400486			
	70	3			•	•		•				•	•			•	•			4072400487			
		5			•	•		•				•	•			•	•			4072400488			
	The rubber oilproof hose is suitable for cleaning metal shavings mixed with traces of oil, dust and conductive materials. It is corrugated externally and smooth on the inside. It has a metal wire to earth the hose. It is connected with two metal connectors through a rivet and covered by a black heat shrink cover. Metal connectors will be marked according to the type of hose. Temperature range - 40° / + 120°C.																						

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

FLEX CONDUCTIVE EXA HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	Abrasion-resistant polyurethane with internal PVC-coated spring steel spiral	Male and female connectors + heat shrink sleeve		•			•	•		•	•		•	•	•	• for EXA machines	4072400451		
		5				•			•	•		•	•		•	•	•		4072400452		
		10				•			•	•		•	•		•	•	•		4072400453		
		15				•			•	•		•	•		•	•	•		4072400454		
	50	3				•			•	•		•	•		•	•	•		4072400455		
		5				•			•	•		•	•		•	•	•		4072400456		
		10				•			•	•		•	•		•	•	•		4072400457		
		15				•			•	•		•	•		•	•	•		4072400458		
	70	3				•			•	•		•	•		•	•	•		4072400667		
		5				•			•	•		•	•		•	•	•		4072400657		
		10				•			•	•		•	•		•	•	•		4072400668		
		15				•			•	•		•	•		•	•	•		4072400669		
	100	3				•			•	•		•	•		•	•	•		4072400670		
		5				•			•	•		•	•		•	•	•		4072400671		
		10				•			•	•		•	•		•	•	•		4072400672		
		15				•			•	•		•	•		•	•	•		4072400673		
The new Flex conductive hose is a conductive hose made of abrasion resistant polyurethane. It is highly suitable in potentially explosive atmospheres for conveying abrasive solids such as dusts and powders. It is black, very flexible and light. It is corrugated externally and smooth on the inside. It will resist from -40 °C to +90 °C. It is connected with two metal connectors through a rivet and covered by a black heat shrink cover. Metal connectors will be marked according to the type of hose.																					

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

POLYURETHANE HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	Polyurethane hose with steel spiral + polyurethane sleeves	40000212			•							•			•	•		•	Z7 22297
		5		40000212			•							•			•	•		•	Z7 22365
		15		40000212			•							•			•	•		•	4072200474
	50	3		40000219			•							•			•	•		•	Z7 22298
		5		40000219			•							•			•	•		•	Z7 22366
		15		40000219			•							•			•	•		•	4072200475
	70	3		Z7 20310			•							•			•	•		•	Z7 22299
		5		Z7 20310			•							•			•	•		•	Z7 22367
		15		Z7 20310			•							•			•	•		•	4072200476
	100	sold by meter, max 15m		not included (P/N to order Z8 40044 - metal tie)			•							•			•	•		•	Z7 24113
The polyurethane hose is suitable for cleaning abrasive materials and liquids. It is transparent with a grey spiral. It is corrugated externally and smooth on the inside. It also has a steel spiral to be connected properly. The hose must be installed so the small arrow on the outside is pointing towards the inlet of the vacuum cleaner. Range of temperature: - 40° / + 90°C.																					

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

FLEX ANTISTATIC EXA HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	PVC with coated spring steel spiral + Stainless Steel AISI 304 hose connectors	Male and female connectors + heat shrink sleeve			•		•	•		•	•			•	•	•	• for EXA machines	4072400459	
		5					•		•	•		•	•			•	•	•		4072400460	
		10					•		•	•		•	•			•	•	•		4072400461	
		15					•		•	•		•	•			•	•	•		4072400462	
	50	3					•		•	•		•	•			•	•	•		4072400463	
		5					•		•	•		•	•			•	•	•		4072400464	
		10					•		•	•		•	•			•	•	•		4072400465	
		15					•		•	•		•	•			•	•	•		4072400466	
	70	3					•		•	•		•	•			•	•	•		4072400674	
		5					•		•	•		•	•			•	•	•		4072400675	
		10					•		•	•		•	•			•	•	•		4072400676	
		15					•		•	•		•	•			•	•	•		4072400677	
	100	3					•		•	•		•	•			•	•	•		4072400678	
		5					•		•	•		•	•			•	•	•		4072400679	
		10					•		•	•		•	•			•	•	•		4072400680	
		15					•		•	•		•	•			•	•	•		4072400681	
The new flex antistatic hose is made with PVC with a coated steel spiral that is properly grounded and connected to metal hose connectors to guarantee the continuity. It is suitable for cleaning abrasive materials and liquids. It is very flexible and light. It is slightly corrugated externally but with a PVC cover and smooth on the inside. Range of temperature: from 0 °C to +85 °C It is connected with two metal connectors through a rivet and covered by a black heat shrink cover. Metal connectors will be marked according to the type of hose.																					

ANTISTATIC NON TOXIC HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE	
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	30	sold by meter	PVC hose with rigid PVC spiral and underlay in transparent polyurethane and copper wire	not included (P/N to order Z8 40040 or Z8 40044 - metal ties)			•									•	•				•	Z7 24054
	40						•								•	•					•	Z7 24028
	50						•								•	•					•	Z7 24029
	70						•								•	•					•	Z7 24030
	100						•									•	•					•
The non-toxic anti-static hose is suitable for cleaning abrasive and granular materials, it is corrugated on the outside and smooth inside. It is suitable for contact with food products as it is FDA approved. It also has a metal spiral to be connected properly. Range of temperature: from - 10 °C to +60 °C.																						

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

SILICONE HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE	
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	sold by meter	White silicone hose with Stainless Steel wire	not included				•				•			•	•				•	Z7 24189	
	50							•				•			•	•					•	4072400220
The silicone hose is designed for cleaning powder from foodstuffs and pharmaceutical mixtures (FDA approved). It is white, resistant to high temperatures (up to 200 °C) and therefore can be sterilized in autoclave (at 121 °C). It has a stainless steel spiral to earth the hose; it is smooth on the inside and slightly smooth externally. Range of temperature: - 60 °C to +200 °C.																						

SILICONE EXA HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE	
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	3M	White silicone hose with Stainless Steel wire + Stainless Steel AISI 304 hose connectors	Male and female connectors + heat shrink sleeve			•	•			•	•		•	•				• for EXA machines	4072400475		
		5M					•	•			•	•		•	•					4072400476		
		10M					•	•			•	•		•	•					4072400477		
		15M					•	•			•	•		•	•					4072400478		
	50	3M					•	•			•	•		•	•		•	•				4072400479
		5M					•	•			•	•		•	•		•	•				4072400480
		10M					•	•			•	•		•	•		•	•				4072400481
		15M					•	•			•	•		•	•		•	•				4072400482
The silicone hose is designed for cleaning powder from foodstuffs and pharmaceutical mixtures (FDA approved). It is white, resistant to high temperatures (up to 200 °C) and therefore can be sterilized in autoclave (at 121 °C). It has a stainless steel spiral to earth the hose; it is smooth on the inside and slightly smooth externally. It is connected with two metal connectors through a rivet and covered with a white heat shrink cover. Metal connectors will be marked according to the type of hose. Range of temperature: - 60 °C to +200 °C.																						

SMOOTH SILICONE HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	White silicone hose with Stainless Steel wire	Integrated sleeves				•			•			•	•				•	4072100135	
		5						•			•			•	•				•	4072100137	
	50	3						•			•			•	•					•	4072100136
		5						•			•			•	•						•
The silicone hose is designed for cleaning powder from foodstuffs and pharmaceutical mixtures (FDA approved). It is white, resistant to high temperatures (up to 200 °C) and therefore can be sterilized in autoclave (at 121 °C). It has a stainless steel spiral to earth the hose; it is smooth both on the inside and externally. Range of temperature: - 60 °C to +200 °C.																					

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

TRANSPARENT FDA HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE		
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	3	Transparent polyurethane FDA hose with steel wire + FDA approved white sleeves	4072000358						•					•	•					•	4072400334	
		5		4072000358							•				•	•					•	4072400336	
		10		4072000358							•				•	•					•	4072400338	
		15		4072000358							•				•	•					•	4072400414	
	50	3		4072000359							•					•	•					•	4072400335
		5		4072000359								•				•	•					•	4072400337
		10		4072000359								•				•	•					•	4072400339
		15		4072000359								•				•	•					•	4072400415
The transparent antistatic hose is the most suitable for the Food & Pharma sectors. It is made with FDA approved material, it is compliant with European Regulations 1935/2004/CE. It is very flexible and light. It is transparent in order to guarantee a better visual check. In case of usage in ATEX environment, the hose has to be connected properly. Temperature range: -40°C / +90°C.																							

TRANSPARENT ANTISTATIC FDA HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE		
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	3	Transparent polyurethane FDA hose with steel wire + FDA approved white sleeves + assembled grounding plates	4072000358			•			•						•	•				•	4072400438	
		5		4072000358			•			•				•	•						•	4072400440	
		10		4072000358			•			•				•	•						•	4072400442	
		15		4072000358			•			•				•	•						•	4072400444	
	50	3		4072000359			•				•				•	•						•	4072400439
		5		4072000359			•				•				•	•						•	4072400441
		10		4072000359			•				•				•	•						•	4072400443
		15		4072000359			•				•				•	•						•	4072400445
The transparent antistatic hose is the most suitable for the Food & Pharma sectors. It is made with FDA approved material, it is compliant with European Regulations 1935/2004/CE. It is very flexible and light. It is transparent in order to guarantee a better visual check. The ground continuity can be guaranteed only by connecting the steel spiral properly so with already assembled grounding plates. Temperature range: -40°C / +90°C.																							

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

TRANSPARENT ANTISTATIC FDA EXA HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE	
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	3M	Transparent antistatic polyurethane with steel wire + Stainless Steel AISI 304 hose connectors	Male and female connectors + heat shrink sleeve			•		•	•		•		•	•					4072400467		
		5M					•		•	•		•	•						4072400468			
		10M					•		•	•		•	•						4072400469			
		15M					•		•	•		•	•						4072400470			
	50	3M					•		•	•		•	•								4072400471	
		5M					•		•	•		•	•								4072400472	
		10M					•		•	•		•	•								4072400473	
		15M					•		•	•		•	•								4072400474	
	70	3M					•		•	•		•	•									4072400643
		5M					•		•	•		•	•									4072400644
		10M					•		•	•		•	•									4072400645
		15M					•		•	•		•	•									4072400646
	100	3M					•		•	•		•	•									4072400647
		5M					•		•	•		•	•									4072400648
		10M					•		•	•		•	•									4072400649
		15M					•		•	•		•	•									4072400650

The transparent antistatic hose is the most suitable for the Food & Pharma sectors. It is made with FDA approved material, it is compliant with European Regulations 1935/2004/CE. It is very flexible and light. It is transparent in order to guarantee a better visual check It is connected with two metal connectors through a rivet and covered with a white heat shrink cover. Metal connectors will be marked according to the type of hose. Temperature range: -40°C / +90°C.

FDA RUBBER HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	White FDA NBR with blue cover	Integrated sleeves	•									•	•					4072400202	
	50	3			•									•	•					4072400201	
Light and flexible hose suitable for food applications.																					

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

STEEL HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3		D50/40 reduction and 40I/40E hose connector included				•					•	•		•	•	•	Z7 22378		
	50	3						•					•	•		•	•	•	Z7 22379		
	40	1	Flexible galvanized steel hose	not included (P/N to order Z8 40040 for D40 and D50, Z8 4044 for D70 and D100 - metal ties)				•					•	•		•	•	•	4072400417		
		3						•					•	•		•	•	•	4072400421		
		5						•					•	•		•	•	•	4072400425		
		10						•					•	•		•	•	•	4072400429		
		15						•					•	•		•	•	•	4072400433		
								•					•	•		•	•	•	4072400437		
	50	1						•					•	•		•	•	•	4072400418		
		3						•					•	•		•	•	•	4072400422		
		5						•					•	•		•	•	•	4072400426		
		10						•					•	•		•	•	•	4072400430		
		15						•					•	•		•	•	•	4072400434		
								•					•	•		•	•	•	4072400438		
	70	1						•					•	•		•	•	•	4072400419		
		3						•					•	•		•	•	•	4072400423		
		5						•					•	•		•	•	•	4072400427		
		10						•					•	•		•	•	•	4072400431		
		15						•					•	•		•	•	•	4072400435		
								•					•	•		•	•	•	4072400439		
	100	1						•					•	•		•	•	•	4072400420		
		3						•					•	•		•	•	•	4072400424		
		5						•					•	•		•	•	•	4072400428		
		10						•					•	•		•	•	•	4072400432		
		15						•					•	•		•	•	•	4072400436		
								•					•	•		•	•	•	4072400440		

The steel hose is recommended for cleaning incandescent and highly-abrasive materials. It is corrugated both externally and on the inside. The 3 m version with metal reductions included should be used with extensions that have the harmonic spring coupling (see chapter 4.b). For hoses by meter, metal reductions are not included. The hose can resist up to 500°C.

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

FLEXIBLE HIGH TEMPERATURE HOSE	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	by meter	Silicone reinforced tissue for high temperatures with galvanized steel spiral	not included (P/N to order 4082300068 for D40, 4082300071 for D50 - metal ties)				•	•	•			•	•		•	•	•		4072400330	
	50	by meter						•	•	•			•	•		•	•	•		4072400331	

The high temperature hose meets any need in ovens cleaning and high temperature material collection. It is corrugated inside and outside, and very flexible and light. It can resist up to 400°C.

HOSES FOR IVT1000	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	32	3	Plastic hose with plastic sleeves	L01716100					•	•					•	•			•		80553100
			Conductive hose with conductive sleeves			•			•	•					•	•			•	•	80552900
			Silicone hose with Stainless Steel ties	Integrated sleeves				•			•				•	•			•		80551900

These hoses are designed specifically for the IVT1000: The **grey plastic hose** is very flexible and light. It is corrugated externally and smooth on the inside. The **black conductive hose** is very flexible and light. It is conductive, corrugated externally and on the inside. These 2 hoses are suitable for cleaning dust and non-abrasive materials. The **white silicone hose** is highly flexible, lightweight and smooth both on the inside and externally. It is ideal for cleaning pharmaceutical powders and mixtures (FDA approved), as it can also be sterilized in an autoclave (at 121° C).

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

CONNECTION EXA HOSES	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES								SECTORS								CODE
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	5	Abrasion-resistant polyurethane with internal PVC-coated spring steel spiral + Stainless Steel AISI 304 hose connector	Male connector + heat shrink sleeve		•			•	•		•	•			•	•	•	• for EXA machines	4072400640	
		3	Transparent antistatic polyurethane with steel wire + Stainless Steel AISI 304 hose connector				•		•	•		•	•			•	•	•		4072400624	
		5					•		•	•		•	•			•	•	•		4072400625	
		10					•		•	•		•	•			•	•	•		4072400626	
		15					•		•	•		•	•			•	•	•		4072400627	
	50	3					•		•	•		•	•			•	•	•		4072400628	
		5					•		•	•		•	•			•	•	•		4072400629	
		10					•		•	•		•	•			•	•	•		4072400630	
		15					•		•	•		•	•			•	•	•		4072400631	
	70	3			Transparent antistatic polyurethane with steel wire + Stainless Steel AISI 304 hose connector			•		•	•		•	•			•	•		•	4072400632
		5						•		•	•		•	•			•	•		•	4072400633
		10						•		•	•		•	•			•	•		•	4072400634
		15						•		•	•		•	•			•	•		•	4072400635
	100	3			Transparent antistatic polyurethane with steel wire + Stainless Steel AISI 304 hose connector			•		•	•		•	•			•	•		•	4072400636
		5						•		•	•		•	•			•	•		•	4072400637
		10						•		•	•		•	•			•	•		•	4072400638
		15						•		•	•		•	•			•	•		•	4072400639
	40	3	Conductive polyurethane hose + Stainless Steel AISI 304 hose connector		•	•							•	•			•	•		•	4072400616
		5			•	•							•	•			•	•		•	4072400617
		10			•	•							•	•			•	•		•	4072400618
		15			•	•							•	•			•	•		•	4072400619

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.a Hoses

CONNECTION EXA HOSES	Ø mm	LENGTH meters	MATERIAL	SLEEVES	FEATURES							SECTORS								CODE	
					OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	EXTREMELY FLEXIBLE	EXTREMELY LIGHT	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	50	3	Conductive polyurethane hose + Stainless Steel AISI 304 hose connector	Male connector + heat shrink sleeve	•	•						•	•			•	•	•	• for EXA machines	4072400620	
		5			•	•						•	•			•	•	•		4072400621	
		10			•	•						•	•			•	•	•		4072400622	
		15			•	•						•	•			•	•	•		4072400623	
	70	3			•	•						•	•			•	•	•		4072400604	
		100			5	•	•						•	•			•	•		•	4072400610
					10	•	•						•	•			•	•		•	4072400611
					15	•	•						•	•			•	•		•	4072400660
	50	5	Smooth black conductive rubber, abrasion resistant		•	•		•					•	•			•	•		•	4072400666
	The connection hoses are made up of 1 male connection and the hose. It has an open bottom. It can be used to connect the hose with an EXA machine and on the other side you can connect the overhead cleaning kit (see page 90), the processing machines of the customer, or separators.																				

(*) **Conductive** A conductive hose is a hose with a volume resistance < 10⁴ ohm. It may have a conductor built in. (**) **Antistatic** An antistatic hose is a hose with a volume resistance < 10⁹ ohm and/or with a conductor built in.

2.b Sleeves

PVC SLEEVES	Ø mm	MATERIAL	FEATURES			SECTORS								COLOUR	CODE
			CONDUCTIVE (*)	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	PVC											 GREY	Z7 23022	
	50													Z7 23023	
	The rigid, grey PVC sleeve connects to the Flex hose.														

RUBBER SLEEVES	Ø mm	MATERIAL	FEATURES			SECTORS								COLOUR	CODE
			CONDUCTIVE (*)	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	RUBBER											■ BLACK	Z7 20001	
	50													Z7 20002	
	70													Z7 20003	
The black rubber sleeve connects to the Air hose.															

POLYURETHANE SLEEVES	Ø mm	MATERIAL	FEATURES			SECTORS							COLOUR	CODE
			CONDUCTIVE (*)	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	CONDUCTIVE POLYURETHANE	•										■ BLACK	40000212
	50		•											40000219
	70		•											Z7 20310
The black polyurethane sleeve is conductive. This sleeve is designed specifically for the polyurethane hose and the conductive polyurethane hose.														

(*) **Conductive** A conductive sleeve is a sleeve with a volume resistance < 10⁴ ohm.

2.a Sleeves

POLYURETHANE SLEEVES	Ø mm	MATERIAL	FEATURES			SECTORS							COLOUR	CODE
			CONDUCTIVE (*)	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	38/40	CONDUCTIVE POLYURETHANE	•										■ BLACK	4072000343
	50		•											Z7 20325
	70		•											
The black polyurethane sleeve is conductive. This sleeve connects to the Flex conductive hose.														

FDA COLOURED POLYURETHANE SLEEVES	Ø mm	MATERIAL	FEATURES			SECTORS								COLOUR	CODE	
			CONDUCTIVE (*)	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	FDA POLYURETHANE		•										 WHITE	4072000358	
				•										 BLUE	4072000363	
				•										 YELLOW	4072000364	
				•										 RED	4072000365	
				•										 GREEN	4072000366	
	50			•											 WHITE	4072000359
				•											 BLUE	4072000367
				•											 YELLOW	4072000368
				•											 RED	4072000369
				•											 GREEN	4072000370
The white FDA polyurethane sleeve is designed for the antistatic FDA transparent hose. Coloured versions are available.																

(*) **Conductive** A conductive sleeve is a sleeve with a volume resistance < 10⁴ ohm.

HOSES AND SLEEVES

Hose connectors and Reductions

Thanks to the range of hose connectors, reductions, bifurcations and trifurcations, the users can find the most appropriate combinations to meet their needs.

You can fit several sections of hose together quickly, to reach various parts of the environment at the same time, or connect Nilfisk hoses to old Nilfisk vacuum cleaners.

Some of the most common example connections can be found at the end of the chapter.



3.a Hose connectors

HOSE FITTING	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	ZINC-PLATED			•				•	•	•		1 internal flange and 1 external flange	Z7 21005
		STAINLESS STEEL AISI 304	•		•				•	•	•	•		Z7 22229
	50	ZINC-PLATED			•				•	•	•			Z7 21003
		STAINLESS STEEL AISI 304	•		•				•	•	•	•		Z7 22230
		STAINLESS STEEL AISI 316L	•			•	•			•	•			4072100139
		STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•			•	•	BLUE		4072400343
			•			•	•			•	•	RED		4072400344
			•			•	•			•	•	YELLOW		4072400345
			•			•	•			•	•	WHITE		4072400346
			•			•	•			•	•	GREEN		4072400347
	70	ZINC-PLATED			•				•	•	•			Z7 21001
		STAINLESS STEEL AISI 304	•		•				•	•	•	•		Z7 22231
		ZINC-PLATED			•				•	•	•			Z7 21040
		STAINLESS STEEL AISI 304	•		•				•	•	•	•		Z7 22232
The hose fitting is an element that lets you connect a hose to any Nilfisk vacuum cleaner that has a quick-fit inlet. Coloured versions have an internal flange with a coloured silicone ring.														

3.a Hose connectors

JOINT/ REDUCER FOR WALL INLET EXA	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	50	STAINLESS STEEL AISI 304	•	•	•	•	•	•	•	•	• for EXA machines		Hole for the EXA connection	4578300103
	70		•	•	•	•	•	•	•	•				4578300102
	50/40		•	•	•	•	•	•	•	•				4578300100
	70/50		•	•	•	•	•	•	•	•				4578300101
	100/70		•	•	•	•	•	•	•	•				4578300104
	These joints and reducers have been developed to connect all EXA certified accessories to the wall inlet of fixed pipings.													

HOSE FITTING WITH FLOW REGULATOR	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	50	ZINC-PLATED			•			•		•			1 internal flange and 1 external flange	Z7 22058
		STAINLESS STEEL AISI 304	•		•			•		•	•			Z7 22221
	70	ZINC-PLATED			•			•		•				Z7 22113
		STAINLESS STEEL AISI 304	•		•			•		•	•			Z7 22222
	100	ZINC-PLATED			•			•		•				Z7 22144
		STAINLESS STEEL AISI 304	•		•			•		•	•			Z7 22206
The hose fitting with flow regulator is a special hose connector which, as well as connecting the hose to a Nilfisk vacuum cleaner, lets you regulate the vacuum power by hand.														

ADAPTER	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	38/40	ZINC-PLATED AND CHROMED COMPONENTS			•			•	•	•			To be used to connect an old Nilfisk machine having the bayonet connection inlet to a Nilfisk IVS hose	Z7 22380
	50/40				•			•	•	•				Z7 22381
	50/50				•			•	•	•				Z7 22382
	38/40	ZINC-PLATED			•			•	•	•			1 external flange and a ball to connect to bayonet coupling, code 22329900	Z7 22355
	50/40				•			•	•	•			1 external flange and a ball to connect to bayonet coupling, code 22344200	Z7 22356
	50/50				•			•	•	•			Z7 22357	
	38	CHROMED			•			•	•	•			Only for old Nilfisk machines having the bayonet connection inlet	22329900
	50				•			•	•	•				22344200
The bayonet coupling adaptor is used to connect an old Nilfisk vacuum cleaner with a Nilfisk hose. An adapter for the Nilfisk bayonet fitting and bayonets only is also available. The bayo adapter is suitable for old Nilfisk machines having the bayonet connection inlet.														

3.a Hose connectors

JUNCTION FITTING	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	ZINC-PLATED			•				•	•	•			Z7 21004
		STAINLESS STEEL AISI 304	•		•				•	•	•	•		Z7 22240
		STAINLESS STEEL AISI 316L	•			•	•					•		4072100140
		STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•				•	 BLUE		4072400348
			•			•	•				•	 RED		4072400349
			•			•	•				•	 YELLOW		4072400350
			•			•	•				•	 WHITE		4072400351
			•			•	•				•	 GREEN		4072400352
	50	ZINC-PLATED			•				•	•	•			Z7 21002
		STAINLESS STEEL AISI 304	•		•				•	•	•	•		Z7 22241
		STAINLESS STEEL AISI 316L	•			•	•					•		4072100141
		STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•				•	 BLUE		4072400353
			•			•	•				•	 RED		4072400354
			•			•	•				•	 YELLOW		4072400355
			•			•	•				•	 WHITE		4072400356
			•			•	•				•	 GREEN		4072400357
	70	ZINC-PLATED			•				•	•	•			Z7 21000
		STAINLESS STEEL AISI 304	•		•				•	•	•	•		Z7 22242
	100	ZINC-PLATED			•				•	•	•			Z7 21041
	The junction fitting is a component used to connect two hoses or a hose and a rubber or plastic accessory/tool. The diameters of the components are the same. Coloured versions have an internal flange with a coloured silicone ring.													

3.a Hose connectors

BENT FITTING	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	ZINC-PLATED			•			•	•	•			2 external flanges	Z7 21013	
		STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 21033	
		STAINLESS STEEL AISI 316L	•			•	•				•			4072100145	
		STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•				•	 BLUE		4072400373	
			•			•	•				•	 RED		4072400374	
			•			•	•				•	 YELLOW		4072400375	
			•			•	•				•	 WHITE		4072400376	
			•			•	•				•	 GREEN		4072400377	
		STAINLESS STEEL AISI 304	•	•	•			•	•	•	• for EXA machines			EXA connection	4072100160
	50	ZINC-PLATED			•			•	•	•			2 external flanges	Z7 21012	
		STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 21034	
		STAINLESS STEEL AISI 316L	•			•	•				•			4072100146	
		STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•				•	 BLUE		4072400378	
			•			•	•				•	 RED		4072400379	
			•			•	•				•	 YELLOW		4072400380	
			•			•	•				•	 WHITE		4072400381	
			•			•	•				•	 GREEN		4072400382	
		STAINLESS STEEL AISI 304	•	•	•			•	•	•	• for EXA machines			EXA connection	4072100161
	70	ZINC-PLATED			•			•	•	•			2 external flanges	Z7 21032	
		STAINLESS STEEL AISI 304	•		•			•	•	•	•			4072100099	
The curved fitting is a component used to fit a hose to a rubber or plastic accessory/tool. It is often used when you have to clean places that are hard to reach. The curved fitting with reduction is a special version of this component. Coloured versions have an internal flange with a coloured silicone ring.															

3.a Hose connectors

BENT FITTING WITH REDUCTION	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40/38	ZINC-PLATED			•				•	•	•		1 external flange	Z7 22358	
		STAINLESS STEEL AISI 304	•		•				•	•	•	•		Z7 22359	
	50/40	ZINC-PLATED			•				•	•	•			Z7 22015	
	70/50				•				•	•	•			Z7 22153	
The curved fitting is a component used to fit a hose to a rubber or plastic accessory/tool. It is often used when you have to clean places that are hard to reach. The curved fitting with reduction is a special version of this component. Coloured versions have an internal flange with a coloured silicone ring.															

QUICK-FIT FITTING	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	ZINC-PLATED			•					•	•		1 quick-fit fitting, 1 external flange	Z7 22186	
	50				•					•	•			Z7 22187	
	70				•					•	•			Z7 22188	
The quick-fit fitting is a simple and quick connector to use between two hoses or a hose and a rubber tool. The quick-fit fitting is always used with a hose connector or, if necessary, a reduction. The diameters of the components may be different.															

EXTENSION FITTING WITH PIN	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40/38	ZINC-PLATED			•					•	•		1 internal flange, 1 quick-fit coupling with harmonic spring, 1 external flange. To use as a connecting element between quick-fit extensions with harmonic springs and coloured floor nozzles and brushes (50 mm diameter)	4072200389	
	50/40				•					•	•		1 quick-fit coupling with harmonic spring. To use as a connecting element between quick-fit extensions with harmonic springs and round brushes (38mm diameter)	4072200387	
	50				•					•	•		1 internal flange, 1 quick-fit coupling with harmonic spring, 1 external flange. To use as a connecting element between quick-fit extensions with harmonic springs and coloured floor nozzles and brushes (50 mm diameter)	4072200388	
	40/38				•					•	•		Lets you fit the old Nilfisk tools	4072200390	
The extension fitting is a special fitting used to connect quick-fit extensions with harmonic springs to specific final accessories/tools. In particular, the extension fitting with reduction (code 4072200390), assembled on the 40mm diameter curved fitting , lets you fit 38 mm diameter old Nilfisk tools.															

3.b Reduction

REDUCTION	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
 	40/32	STAINLESS STEEL AISI 304	•		•			•	•	•	•		1 internal flange, 1 external flange	Z7 22347
	50/32	ZINC-PLATED			•			•	•	•				Z7 22313
	50/32	STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 22346
	50/40	ZINC-PLATED			•			•	•	•				Z7 22000
		STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 22223
		STAINLESS STEEL AISI 316L	•			•	•				•			4072100142
		STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•				•	■ BLUE		4072400358
			•			•	•				•	■ RED		4072400359
			•			•	•				•	■ YELLOW		4072400360
			•			•	•				•	■ WHITE		4072400361
			•			•	•				•	■ GREEN		4072400362
		STAINLESS STEEL AISI 304	•	•	•			•	•	•	• for EXA machines		EXA connection	4072100153
	70/40	ZINC-PLATED			•								1 internal flange, 1 external flange	Z7 22002
		STAINLESS STEEL AISI 304	•		•						•			Z7 22224
		STAINLESS STEEL AISI 316L	•			•	•				•			4072100143
		STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•				•	■ BLUE		4072400363
			•			•	•				•	■ RED		4072400364
			•			•	•				•	■ YELLOW		4072400365
			•			•	•				•	■ WHITE		4072400366
			•			•	•				•	■ GREEN		4072400367
		STAINLESS STEEL AISI 304	•	•	•			•	•	•	• for EXA machines		EXA connection	4072100154

3.b Reduction

REDUCTION	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
 	70/50	ZINC-PLATED			•				•	•	•			1 internal flange, 1 external flange	Z7 22001
		STAINLESS STEEL AISI 304	•		•				•	•	•	•			Z7 22225
		STAINLESS STEEL AISI 316L	•			•	•				•				407210014
	70/50	STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•				•	 BLUE			407240036
			•			•	•				•	 RED			407240036
			•			•	•				•	 YELLOW			407240037
			•			•	•				•	 WHITE			407240037
			•			•	•				•	 GREEN			407240037
		STAINLESS STEEL AISI 304	•	•	•				•	•	•	• for EXA machines		EXA connection	407210015
	100/50	ZINC-PLATED			•				•	•	•			1 internal flange, 1 external flange	Z7 22126
		STAINLESS STEEL AISI 304	•		•				•	•	•	•			Z7 22226
			•	•	•				•	•	•	• for EXA machines		EXA connection	407210015
	100/70	ZINC-PLATED			•				•	•	•			1 internal flange, 1 external flange	Z7 22125
		STAINLESS STEEL AISI 304	•		•				•	•	•	•			Z7 22227
			•	•	•				•	•	•	• for EXA machines		EXA connection	407210015
The reduction is a fitting that goes between a vacuum cleaner with a quick-fit inlet and a hose that has a smaller diameter than the inlet. The diameters of the components are different.															

3.b Reduction

REDUCTION WITH FLOW REGULATOR	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	50/40	ZINC-PLATED			•				•	•	•			1 internal flange, 1 external flange	Z7 22112
			•		•				•	•	•	•			Z7 22234
		STAINLESS STEEL AISI 304	•	•	•				•	•	•	• for EXA machines		EXA connection	4072400665
	70/40	ZINC-PLATED			•				•	•	•			1 internal flange, 1 external flange	Z7 22164
		STAINLESS STEEL AISI 304	•		•				•	•	•	•			Z7 22235
	70/50	ZINC-PLATED			•				•	•	•				Z7 22162
			•		•				•	•	•	•			Z7 22236
		STAINLESS STEEL AISI 304	•	•	•				•	•	•	• for EXA machines		EXA connection	4072400605
	100/50	ZINC-PLATED			•				•	•	•				Z7 22165
	100/70				•				•	•	•				Z7 22163
	The reduction with flow regulator is a special reduction which, as well as connecting the vacuum cleaner to a hose (with a smaller diameter than the inlet), lets you regulate the vacuum power by hand.														

3.b Reduction

BIFURCATION	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40/40/40	ZINC-PLATED			•				•	•	•			1 internal flange	Z7 22061
		STAINLESS STEEL AISI 304	•		•				•	•	•	•			Z7 22145
	50/50/50	ZINC-PLATED			•				•	•	•				Z7 22059
		STAINLESS STEEL AISI 304	•		•				•	•	•	•			Z7 22146
		STAINLESS STEEL AISI 316L	•			•	•				•				4072100147
		STAINLESS STEEL AISI 316L + COLOURED SILICONE RING	•			•	•				•	 BLUE			4072400383
			•			•	•				•	 RED			4072400384
			•			•	•				•	 YELLOW			4072400385
			•			•	•				•	 WHITE			4072400386
			•			•	•				•	 GREEN			4072400387
		STAINLESS STEEL AISI 304	•	•	•			•	•	•	• for EXA machines		EXA connection	4072100158	
	70/70/70	ZINC-PLATED			•				•	•	•			1 internal flange	Z7 22110
		STAINLESS STEEL AISI 304	•		•				•	•	•	•			Z7 22282
			•	•	•			•	•	•	• for EXA machines		EXA connection	4072100159	
		ZINC-PLATED			•				•	•	•			1 internal flange	Z7 22135
	100/100/100	STAINLESS STEEL AISI 304	•		•			•	•	•	•		Z7 22157		
The bifurcation is a fitting used to connect the vacuum cleaner to two different hoses or, between hoses in general. Coloured versions have an internal flange with a coloured silicone ring.															

3.b Reduction

BIFURCATION WITH REDUCTION	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40/32/32	ZINC-PLATED			•			•	•	•			1 internal flange	Z7 22253	
	50/32/32				•			•	•	•				Z7 22254	
	50/40/40				•			•	•	•				Z7 22060	
	50/40/40	STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 22261	
	70/32/32	ZINC-PLATED			•			•	•	•				Z7 22252	
	70/40/40				•			•	•	•				Z7 22111	
	70/40/40	STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 22262	
	70/50/50	ZINC-PLATED			•			•	•	•				Z7 22064	
		STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 22263	
	100/50/50	ZINC-PLATED			•			•	•	•				Z7 22128	
	100/70/70				•			•	•	•				Z7 22127	
	100/70/70	STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 22307	
The bifurcation with reduction is a special bifurcation which, as well as letting you clean in two different places, connects the vacuum cleaner to two hoses of a smaller diameter than the inlet on the machine. Alternatively you can connect a hose to two others with smaller diameters than the first.															

BIFURCATION WITH FLOW REGULATOR	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40/40/40	ZINC-PLATED			•			•	•	•			1 internal flange	Z7 22114	
	50/50/50				•			•	•	•				Z7 22056	
		STAINLESS STEEL AISI 304	•		•			•	•	•	•				Z7 22250
The bifurcation with flow regulator is a special bifurcation which, a well as letting you clean in two different places, also lets you regulate the vacuum power of both tools.															

3.b Reduction

BIFURCATION WITH REDUCTION AND FLOW REGULATOR	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	50/40/40	ZINC-PLATED			•			•	•	•			1 internal flange	Z7 22057	
	70/50/50				•			•	•	•				Z7 22065	
		STAINLESS STEEL AISI 304	•		•			•	•	•	•			Z7 22249	
	100/50/50	ZINC-PLATED			•			•	•	•				Z7 22130	
	100/70/70				•			•	•	•				Z7 22129	
The bifurcation with reduction and flow regulator is a bifurcation with reduction for cleaning in two different places, and the vacuum power can be regulated manually for each tool.															

TRIFURCATION	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	50/50/50/50	ZINC-PLATED			•			•	•	•			1 internal flange	ZS07RW22027	
The trifurcation is a fitting used to connect the vacuum cleaner to three different hoses or, between hoses in general. The trifurcation lets you clean in three different places using the same vacuum cleaner.															

TRIFURCATION WITH FLOW REGULATOR	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	50/50/50/50	ZINC-PLATED			•			•	•	•			1 internal flange	Z7 22179	
	The trifurcation with flow regulator is a special trifurcation which, a well as letting you clean in three different places, also lets you regulate the vacuum power of all three tools.														

3.b Reduction

TRIFURCATION WITH REDUCTION	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	50/40/40/40	ZINC-PLATED			•			•	•	•			1 internal flange	Z7 22260
	70/50/50/50				•			•	•	•				Z7 22259
	100/50/50/50				•			•	•	•				ZS07IS22105
	The trifurcation with reduction is a special trifurcation which, as well as letting you clean in three different places, connects the vacuum cleaner to three hoses of a smaller diameter than the inlet on the machine. It can also be used to connect a hose to three other hoses of a smaller diameter.													

3.c Examples: hose connectors and reductions




Ø 40 mm
Nilfisk
inlet

A



Ø 40 mm
Hose fitting
Z7 21005

C



Ø 40 mm
3-meter Rubber Hose with sleeves
Z7 24005




Ø 70 mm
Nilfisk
inlet

A




Ø 70/50 mm
Reduction
Z7 22001

C




Ø 50 mm
3-meter conductive Flex Hose with sleeves
Z7 24053

A




Ø 70/70/70 mm
Bifurcation
Z7 22110

C




Ø 70 mm
3-meter Polyurethane Hose with sleeves
Z7 22367

C




Ø 40 mm
3-meter Flex Hose with sleeves
Z7 22150

E



Ø 40 mm
Curved fitting
Z7 21013


3.c Examples: hose connectors and reductions




Ø 50 mm
3-meter Air Hose with sleeves
Z7 22062



Ø 50 mm
Junction Fitting
Z7 21002




Ø 50 mm
3-meter Air Hose with sleeves
Z7 22062




Ø 50 mm
3-meter Air Hose with sleeves
Z7 22062



Ø 50 mm
Hose fitting
Z7 21003



Ø 50 mm
Quick-fit fitting
Z7 22187



Ø 50 mm
3-meter Air Hose with sleeves
Z7 22062



Ø 50 mm
Old Nilfisk
inlet
Ø 38 mm
Old Nilfisk
inlet
Ø 50 mm
Old Nilfisk
inlet




Ø 50/40 mm
Complete bayonet coupling
adaptor **Z7 22381**
Ø 38/40 mm
Complete bayonet coupling
adaptor **Z7 22380**
Ø 50/50 mm
Complete bayonet coupling
adaptor **Z7 22382**



Ø 40 mm
3-meter conductive Polyurethane Hose with sleeves
Z7 22368
Ø 38 mm
3-meter conductive Flex Hose with sleeves
Z7 22374
Ø 50 mm
3-meter Rubber Hose with sleeves
Z7 24003

3.c Examples: hose connectors and reductions




Ø 70 mm
EXA Machine
inlet

C




Ø 70/40 mm
Reduction
4072100154

B




Ø 40 mm
3-meter Flex Antistatic Hose
4072400459



Ø 70 mm
EXA Machine
inlet

D



Ø 70/70/70 mm
Reduction
4072100159

B



Ø 70 mm
5-meter Transparent Antistatic Hose
4072400644

C




Ø 70/50 mm
Reduction
4072100155

B



Ø 50 mm
3-meter Flex Conductive Hose
4072400455



Ø 40 mm
EXA Machine
inlet

B




Ø 40 mm
3-meter flex conductive hose
4072400451

F



Ø 40 mm
Bent Fitting
4072100160

3.c Examples: hose connectors and reductions



Ø 50 mm
EXA Machine
inlet

B



Ø 50 mm
3-meter Flex Conductive Hose
4072400455

B



Ø 50 mm
3-meter Flex Conductive Hose
4072400455

Handgrips and Extensions

The handgrips are essential for cleaning floors and should be used with the floor nozzle.

Fitted with a quick-fit coupling, the handgrips can be fitted to the floor nozzle quickly and simply.

The extensions are tubular elements for cleaning walls and other overhead areas in general.

Different kinds of extensions are available: dedicated extensions for cleaning ovens (with sliding PTFE sleeve) and those for cleaning pipes in raised areas.

In the last section you will find some of the possible connection schemes between handgrips and floor nozzles, and between extensions and different final tools/accessories.



4.a Handgrips

HANDGRIP	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	ZINC-PLATED			•			•	•	•			1 quick-fit fitting	Z7 22121
		ALUMINIUM			•			•	•	•				Z7 22026
		STAINLESS STEEL AISI 304	•		•			•	•	•	•			40000215
		STAINLESS STEEL AISI 316L	•			•	•				•			4072200596
			•			•	•				•	■ BLUE		4072400398
			•			•	•				•	■ RED		4072400399
			•			•	•				•	■ YELLOW		4072400400
			•			•	•				•	■ WHITE		4072400401
			•			•	•				•	■ GREEN		4072400402
			•			•	•				•			
		STAINLESS STEEL AISI 304	•	•	•			•	•	•	• for EXA machines		EXA connection	4072000385
	50	ZINC-PLATED			•			•	•	•			1 quick-fit fitting	Z7 22122
		ALUMINIUM						•	•	•				Z7 22025
		STAINLESS STEEL AISI 304	•					•	•	•	•			40000222
		STAINLESS STEEL AISI 316L	•			•	•				•			4072200597

4.a Handgrips

HANDGRIP	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	50	STAINLESS STEEL AISI 316L	•			•	•				•	 BLUE	1 quick-fit fitting	4072400403
			•			•	•				•	 RED		4072400404
			•			•	•				•	 YELLOW		4072400405
			•			•	•				•	 WHITE		4072400406
			•			•	•				•	 GREEN		4072400407
		STAINLESS STEEL AISI 304	•	•	•			•	•	•	• for EXA machines		EXA connection	4072000386
	70	ALUMINIUM	•		•			•	•	•			1 quick-fit fitting	Z7 22091
The handgrip is essential for cleaning floors; it is the element which fits between the hose sleeve and floor nozzle. It has a quick-fit fitting and is available in various materials and diameters. Coloured versions have an internal flange with a coloured silicone ring.														


EXTENSION WITH QUICK-FIT FITTING	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	ALUMINIUM			•			•	•	•			1 quick-fit fitting, 1 internal flange	Z7 22008
					•			•	•	•				Z7 22007
					•			•	•	•				Z7 22006
					•			•	•	•				Z7 22270
					•			•	•	•				Z7 22267
					•			•	•	•				Z7 22036
	50				•			•	•	•				Z7 22005
					•			•	•	•				Z7 22004
					•			•	•	•				Z7 22003
					•			•	•	•				Z7 22271
					•			•	•	•				Z7 22268
					•			•	•	•				Z7 22037
					•			•	•	•				
The aluminium extensions with quick-fit fittings are available in three different lengths, letting you attach final tools (make sure you remove the harmonic spring, if present) to clean high areas, pipes and walls. Thanks to the internal groove, these extensions can easily be connected together.														

4.a Handgrips


EXTENSION WITH QUICK-FIT COUPLING	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	ALUMINIUM			•				•	•	•			1 quick-fit coupling with harmonic spring	Z7 22386
		STAINLESS STEEL AISI 304		•	•				•	•	•	• for EXA machines		EXA connection	4072400658
	50	ALUMINIUM			•				•	•	•			1 quick-fit coupling with harmonic spring	Z7 22385
		STAINLESS STEEL AISI 304		•	•				•	•	•	• for EXA machines		EXA connection	4072400659
	40	PTFE												Resistant to high temperatures. To use with quick-fit extensions with harmonic springs	Z7 20327
	50												Z7 20326		
			STAINLESS STEEL AISI 304												For quick-fit coupling
The aluminium extensions with quick-fit fittings and harmonic spring are 1 meter long, but can be easily extended as they are easy to fit together, with a hole on one end and a harmonic spring on the other. As well as their use for cleaning suspended parts (e.g. with coloured brushes together with the 50mm coupling, code 4072200388, or the 50/40mm coupling, code 4072200387), when combined with the PTFE sliding sleeve and the floor nozzle with silicone strip (cf. chap. 5.a) they are suitable for cleaning ovens (cf. chap 7, Oven Cleaning Kit).															

EXTENSION HANDGRIP FOR IVT1000	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	32	STAINLESS STEEL AISI 316						•						The kit consists of two extensions made of AISI 316 steel	11112500
														Connecting tube made of AISI316 steel	11882505
	The 32mm diameter stainless-steel extensions should only be used with the IVT1000 vacuum cleaner. The two available extensions can easily be connected together (conical type connection). The 250mm long tube (32mm diameter) is also only for the IVT1000. Made of stainless steel, it connects the hose to the final tool/accessory.														

4.b Examples: **handgrips** and **extensions**




Ø 40 mm
3-meter conductive Flex
Hose with sleeves
Z7 22150



Ø 40 mm
Sleeve
Z7 22121



Ø 40 mm
Wheeled floor nozzle for dust and
liquids (400 mm)
Z7 22030




Ø 50 mm
3-meter Air Hose with
sleeves **Z7 22062**
Ø 40 mm
3-meter Air Hose with
sleeves **Z7 22049**



Ø 50 mm
Extensions with quick-fit fitting (3 meters) **Z7 22003**
Ø 40 mm
Extensions with quick-fit fitting (3 meters) **Z7 22006**



Ø 50 mm
Wall brush (400 mm)
Z7 22198



Ø 38 mm
3-meter conductive Flex
Hose with sleeves
Z7 22374






Ø 40 mm
Quick-fit extensions with harmonic spring
Z7 22386




Ø 40 mm
Wall brush (300 mm)
Z7 22194

4.b Examples: handgrips and extensions


- | | | | |
|--|--|---|--|
| <p>C</p>  <p>Ø 40 mm
3-meter Air Hose
with sleeves
Z7 22049</p> | <p>D</p>  <p>Ø 40 mm
Quick-fit extensions with harmonic spring
Z7 22386</p> | <p>A</p>  <p>Ø 50/40 mm
Extension fitting
with reduction
4072200387</p> | <p>I</p>  <p>Ø 50 mm
Curved brush for pipes (300 mm)
22432600</p> |
| <p>C</p>  <p>Ø 50 mm
3-meter Polyurethane
Hose with sleeves
Z7 22298</p> | <p>D</p>  <p>Ø 50 mm
Quick-fit extensions with harmonic spring
Z7 22385</p> | <p>A</p>  <p>Ø 50 mm
Extension fitting
with reduction
4072200388</p> | <p>J</p>  <p>Ø 50 mm
Brush for flat surfaces (300 mm)
22432905</p> |

4.b Examples: handgrips and extensions



B

Ø 40 mm
3-meter Flex Conductive
Hose
4072400451




G

Ø 40 mm
EXA handgrip
4072000385



K

Ø 40 mm
Wheeled floor nozzle for dust and
liquids (400 mm)
4072000387



B

Ø 40 mm
3-meter Flex Conductive Hose
4072400451



E

Ø 40 mm
EXA extension
4072400658



K

Ø 40 mm
Mobile coloured floor nozzle (400 mm)
4072400587

Floor nozzles and Brushes

The floor nozzles are used to clean solids and liquids from all types of surfaces. As well as the floor nozzles, brushes are also available to clean dust off floors and other surfaces such as walls and pipes.

The brushes only have bristles, while the floor nozzles have both rubber lips and bristle profiles.

Most Nilfisk floor nozzles and brushes come with certifications (e.g. FDA approval).



5.a Floor nozzles

MOBILE FLOOR NOZZLE FOR DUST AND LIQUIDS	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	300	ZINC-PLATED			•				•		•		With two rubber lips (silicone for the stainless steel version), wheel adjuster screw and 1 internal flange	Z7 22171	
		400				•				•		•			Z7 22030	
		400	ZINC-PLATED + SILICONE LIPS							•	•				Anti-Shock Version With Silicone Lips	4072200651
		400	STAINLESS STEEL			•				•		•		With two rubber lips (silicone for the stainless steel version), wheel adjuster screw and 1 internal flange	40000216	
		400			•	•			•		•	•	•		for EXA machines	4072000387
	50	300	ZINC-PLATED			•				•		•		With two rubber lips (silicone for the stainless steel version), wheel adjuster screw and 1 internal flange	Z7 22172	
		400				•				•		•			Z7 22029	
		400	ZINC-PLATED + SILICONE LIPS							•	•				Anti-Shock Version With Silicone Lips	4072200650
		400	STAINLESS STEEL			•				•		•		With two rubber lips (silicone for the stainless steel version), wheel adjuster screw and 1 internal flange	40000223	
		400			•	•			•		•	•	•		for EXA machines	4072000388
		500	ZINC-PLATED			•				•		•		With two rubber lips (silicone for the stainless steel version), wheel adjuster screw and 1 internal flange	Z7 22147	
		500				•				•	•	•			Z7 22092	
	70	500				•				•	•	•			Z8 20123	
	40					•				•		•			Z8 20295	
		300/400	RUBBER (rubber lips 10 pieces)			•				•		•			Z8 20296	
		500				•				•		•				
The wheeled floor nozzle, with rubber profile on the zinc-plated version and silicone profile on the stainless steel version, is ideal for cleaning dust and liquids. Thanks to the internal flange it is very easy to connect to the handgrips (cf. chapter 4.a). The new anti-shock versions have been implemented to be used in the B&C sector in order to dissipate any static charges caused by the passage of dust.																

5.a Floor nozzles

MOBILE COLOURED NOZZLES FOR DUST AND LIQUIDS	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL												
 	40	400	AISI 316 + SILICONE FDA COVER	•			•	•						TRANSPARENT	EXA connection	4072400314	
				•			•	•						BLUE		4072400315	
				•			•	•						RED		4072400316	
				•			•	•						GREEN		4072400317	
				•			•	•						YELLOW		4072400318	
	50			•			•	•						WHITE		4072400319	
				•			•	•						TRANSPARENT		4072400320	
				•			•	•						BLUE		4072400321	
				•			•	•						RED		4072400322	
				•			•	•						GREEN		4072400323	
				•			•	•						YELLOW		4072400324	
				•			•	•						WHITE		4072400325	
	40	400	AISI 316 + SILICONE FDA COVER	•	•		•	•						TRANSPARENT	EXA connection	4072400587	
				•	•		•	•						BLUE		4072400588	
				•	•		•	•						RED		4072400589	
				•	•		•	•						GREEN		4072400590	
				•	•		•	•						YELLOW		4072400591	
				•	•		•	•						WHITE		4072400592	
				50	•	•		•	•							TRANSPARENT	4072400593
					•	•		•	•							BLUE	4072400594
				50	•	•		•	•							RED	4072400595
					•	•		•	•							GREEN	4072400596
		50	•	•		•	•						YELLOW	4072400597			
			•	•		•	•						WHITE	4072400598			
			SILICONE COVER											TRANSPARENT	Spare parts valid for standard coloured nozzle and EXA version too	4082300062	
													BLUE	4082300063			
													RED	4082300064			
												GREEN	4082300065				
												YELLOW	4082300066				
												WHITE	4082300067				
		Silicone wheel													4082300061		
The coloured floor nozzle can be used to apply the colour coded program in the food & pharma sectors.																	

5.a Floor nozzles

COLOURED NOZZLE	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL												
	40	400	AISI 316 + NBR FDA COVER				•	•						 BLUE		4072400304	
							•	•							 RED		4072400305
							•	•							 GREEN		4072400306
							•	•							 YELLOW		4072400307
							•	•							 WHITE		4072400308
	50						•	•							 BLUE		4072400309
							•	•							 RED		4072400310
							•	•							 GREEN		4072400311
							•	•							 YELLOW		4072400312
							•	•							 WHITE		4072400313
			SILICONE				•	•						Silicone lip	Z8 20255		
Stainless steel nozzle with coloured cover to be used in the food sector to apply the colour coded program.																	

WHEELED FLOOR NOZZLE FOR DUST	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS						COLOR	NOTES	CODE		
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	300	ZINC-PLATED			•			•		•				With two brush lips, wheel adjuster screw and 1 internal flange	Z7 22174
		400				•			•		•			Z7 22138		
	50	300				•			•		•					Z7 22175
		400				•			•		•					Z7 22137
		500				•			•		•					Z7 22148
	70	500				•			•		•					Z7 22149
		300/400	BRUSH STRIPS													Z8 23040
		500													Z8 23041	
	The wheeled floor nozzle with bristle profile is ideal for cleaning dust. Thanks to the internal flange it is very easy to connect to the handgrips (cf. chapter 4.a).															

5.a Floor nozzles

NOZZLE FOR OVENS	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	400	ZINC-PLATED			•	•					•		With two silicone lips, wheel adjuster screw, 1 internal flange and harmonic spring quick-fit coupling	Z7 22272	
	50					•	•					•			Z7 22273	
	40	400	ALUMINIUM			•	•					•		1internal flange and 1 quick-fit coupling with harmonic spring	Z7 22031	
	50					•	•					•			Z7 22032	
	40	400	AISI 316 BASE WITH HEAT RESISTANT COVER				•					•		1 internal flange	4072400326	
	50						•					•			4072400327	
		500	SILICONE											Silicone lip	Z8 20255	
The nozzles for cleaning ovens are special components resistant to high temperatures. There are two versions available: the first has wheels and silicone lips, the second is made completely of aluminium. Both have quick-fit couplings with harmonic spring so they can easily be connected to the extensions, which also have harmonic spring quick-fit couplings, as shown in chapter 4.b.																

NOZZLE FOR BUSES	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	50	200	ALUMINIUM			•						•			"C" bristle profile and 1 internal flange	Z7 22170
The nozzle for buses, thanks to its compact dimensions and "C" bristle profile is ideal for cleaning the corridors of buses. Made entirely of aluminium, it has an internal flange for the quick-fit coupling with the relevant handgrip (cf. chapter 4.a).																

5.a Floor nozzles

FLOOR NOZZLE FOR LIQUIDS	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	400	ZINC-PLATED			•						•			With two lips made of rubber (silicone for the stainless steel version), two Nylon shoes and 1 internal flange	Z7 22028
			STAINLESS STEEL			•							•			Z7 22296
		500	ZINC-PLATED			•							•			Z7 22168
	50	400	ZINC-PLATED			•							•			Z7 22027
			STAINLESS STEEL			•							•			Z7 22294
		500	ZINC-PLATED			•							•			Z7 22167
		400	RUBBER LIPS			•							•		Rubber lip	Z8 20086
		500														Z8 20087
The floor nozzles for liquids are suitable for cleaning liquids off floors. They have two rubber lips, or silicone lips on the stainless steel versions. They are easy to connect to the handgrips thanks to the internal groove on the fitting of the floor nozzle.																

FIXED FLOOR NOZZLE	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL												
	70	600	ZINC-PLATED			•						•			With two lips made of rubber and two wheels	Z7 22085	
						•							•			For S2/S3 model	4056000487
						•							•			For CTS model	4056000393
	50	500				•							•			With two lips made of rubber and two wheels	Z7 22086
						•							•			For D400 Platform	4072200695
			RUBBER												Rubber lip 600-700 mm	Z8 20297	
The fixed floor nozzle is a special floor nozzle ideal for cleaning dust on large surface areas. The fixed floor nozzle has two rubber lips and two wheels. It is very easy to connect it to the vacuum cleaner thanks to the 70mm diameter quick-fit fitting.																	

5.a Floor nozzles

FLOOR NOZZLE FOR IVT1000	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	32	300	STAINLESS STEEL + POLYPROPYLENE	•				•							Bristle profile and stainless steel coupling	22431611
				•				•						22431608		
				•				•							Silicone profile, FDA approved and stainless steel coupling	22430808
These three floor nozzles are designed specifically for the IVT1000 vacuum cleaner. As well as the standard version and the antistatic version there is also a model with a silicone profile, approved by the FDA and suitable for autoclaves. All three floor nozzles are suitable for cleaning dust.																

5.b Brushes

BRUSH	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL												
	40	220	PVC BRUSH + METAL CONNECTION			•						•				Z7 22042	
		300				•						•				Z7 22043	
		400				•						•				Z7 22044	
	50	220				•							•				Z7 22038
		300				•							•				Z7 22039
		400				•							•				Z7 22040
		500				•							•				Z7 22041
	70	300				•							•				Z7 22077
		400				•							•				Z7 22078
		500				•							•				Z7 22093
		40		220			•							•			
300					•							•				Z7 22194	
400					•							•				Z7 22195	
50		220			•							•				Z7 22196	
		300			•							•				Z7 22197	
		400			•							•				Z7 22198	
		500			•							•				Z7 22199	
		220			•							•				Z8 23009	
		300			•							•				Z8 23010	
		400			•							•				Z8 23011	
		500			•							•				Z8 23012	

The rectangular-section 90° brushes are ideal for removing and cleaning dust from floors, while the 30° brushes are ideal for cleaning walls. Both types, with a PVC structure, have a black bristle profile. The 90° brushes connect to the handgrips described in chapter 4.a, while the wall brushes connect to the extensions described in chapter 4.b (in particular, when used with the quick-fit extensions, remember to always remove the harmonic spring from the brushes).

5.b Brushes

CURVED BRUSH FOR PIPES	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	100	PVC BRUSH			•							•			Z7 22132
		200				•							•			Z7 22134
	50	100				•							•			Z7 22131
		200				•							•			Z7 22133
		100				•							•			Z8 24042
		200				•							•			Z8 24043
The curved brush is designed for cleaning pipes, especially in suspended installations. Its rounded shape makes it particularly effective for removing and cleaning dust. This element must be used with the extensions described in chapter 4.b (in particular, when used with the quick-fit extensions, remember to always remove the harmonic spring from the brushes).																


NOZZLE FOR FLAT SURFACES	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	50	300	POLYPROPYLENE										•			22432306
	50	300											•			22432302
		300											•			32430806
		300											•			32430802
			ZINC-PLATED										•			10645031
			STAINLESS STEEL										•			10645011
The coloured nozzles for flat surfaces with rubber lip are specific nozzles for environments where foodstuffs and pharmaceuticals are processed (in particular for cleaning high areas). Available in the autoclave and conductive versions, all FDA approved, these nozzles come in three colours: green, grey and black (conductive version). Thanks to the swivel fitting (to connect to quick-fit extensions with harmonic spring using the 50/40mm reduction, code 4072200387, or with a 50mm extension fitting, code 4072200388), the manoeuvrability and functionality are unbeatable.																

5.b Brushes

BRUSH FOR FLAT SURFACES	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE	
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL												
	50	300	POLYPROPYLENE								•			BRUSH FOR FLAT SURFACES: bristle profile, FDA approved, black	22432902		
														•		BRUSH FOR FLAT SURFACES: bristle profile, FDA approved, grey	22432900
														•		BRUSH FOR FLAT SURFACES: bristle profile, suitable for autoclaves, FDA approved, blue	22432907
														•		BRUSH FOR FLAT SURFACES: bristle profile, suitable for autoclaves, FDA approved, red	22432905
														•		BRUSH FOR FLAT SURFACES: bristle profile, suitable for autoclaves, FDA approved, green	22432906
														•		BRUSH SPARE PARTS: black, the floor nozzle fitting is not included	42431602
														•		BRUSH SPARE PARTS: blue, the floor nozzle fitting is not included	42431607
														•		BRUSH SPARE PARTS: red, the floor nozzle fitting is not included	42431605
														•		BRUSH SPARE PARTS: green, the floor nozzle fitting is not included	42431606
														•		BRUSH SPARE PARTS: yellow, the floor nozzle fitting is not included	42431604
	50		ZINC-PLATED									•		BRUSH FITTING SPARE PARTS: swivel fitting	10645031		
			STAINLESS STEEL									•			10645011		
The coloured brushes for flat surfaces, with a bristle profile, are also designed for cleaning environments where foodstuffs and pharmaceuticals are processed, especially for cleaning high areas. These brushes, available in various colours, are suitable for autoclaves and are FDA approved. With a swivel fitting, these brushes must be used with quick-fit extensions with harmonic spring and the relevant fittings (with 50/40mm reduction and harmonic spring or 50mm fitting with harmonic spring).																	

CURVED BRUSH FOR PIPES	Ø mm	LENGTH millimeters	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
				AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	50	100	POLYPROPYLENE									•		CURVED BRUSH FOR PIPES: bristle profile, FDA approved, black	22432402	
		200											•			22432502
		300											•			22432602
	100											•		CURVED BRUSH SPARE PARTS: black, the brush fitting is not included	42430902	
	200											•			42431002	
	300											•			42431102	
	50		ZINC-PLATED										•		BRUSH FITTING SPARE PARTS: swivel fitting	10645031
			STAINLESS STEEL										•			10645011
The curved, coloured brushes for pipes, with a bristle profile, are ideal for cleaning dust off pipes in suspended installations. Available in two colours, grey and black (conductive version), and in three sizes, they are FDA approved. With a swivel fitting, these brushes must be used with quick-fit extensions with harmonic spring and the relevant fittings (with 50/40mm reduction and harmonic spring or 50mm fitting with harmonic spring).																

5.c Examples: **Floor nozzles** and **Brushes**




Ø 40 mm
Handgrip
Z7 22121



Ø 40 mm
Floor nozzle for liquids (400 mm) **Z7 22296**

Ø 40 mm
Wheeled floor nozzle for dust (500 mm) **Z7 22138**



Ø 50 mm
Handgrip
40000222



Ø 50 mm
Floor brush (300 mm)
Z7 22039


5.c Examples: Floor nozzles and Brushes



Ø 40 mm

Quick-fit extensions with harmonic spring

Z7 22386



Ø 40 mm

Curved brush for pipes (200 mm)

Z7 22134



Ø 40 mm

Quick-fit extensions with harmonic spring

7 22386



Ø 40/50 mm

Extension fitting with reduction

4072200387



Ø 50 mm

Nozzle for flat surfaces (300 mm)

22432302



Ø 50 mm

Quick-fit extensions with harmonic spring

7 22385



Ø 50 mm

Extension fitting

4072200388




Ø 50 mm

Nozzle for flat surfaces (300 mm)

22432302

5.c Examples: Floor nozzles and Brushes



Ø 40 mm

Sliding PTFE sleeve

7 20327



Ø 40 mm

Quick-fit extensions with harmonic spring

7 22386



Ø 40 mm

Wheeled nozzle for ovens (400 mm)


7 22272



Ø 40 mm

Nozzle for ovens (400 mm)

7 22031



Ø 40 mm

EXA handgrip

4072000385



Ø 40 mm

Mobile coloured floor nozzle (400 mm)

4072400587

Final tools

All the final tools/accessories such as rubber and antistatic rubber cones, natural- and Nylon-bristle round brushes, zinc-plated and stainless-steel flat-tip crevice nozzles are grouped together in the category “Final tools”.

Successful cleaning also depends on these elements.



6.a Rubber tools

CONE	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
  	40	NBR			•			•	•	•	•			Z7 21011
		CONDUCTIVE NBR			•			•	•	•	•			40000214
		STAINLESS STEEL + CONDUCTIVE NBR		•	•			•	•	•	• for EXA machines		Oilproof	4072400505
		SILICONE	•		•	•						TRANSPARENT		4072100105
			•		•	•						BLUE		4072100106
			•		•	•						RED		4072100107
			•		•	•						GREEN		4072100108
			•		•	•						YELLOW		4072100109
			•		•	•						WHITE		4072100110
		STAINLESS STEEL AISI 304 + SILICONE	•	Only dust, II 2D	•	•					• for EXA machines	TRANSPARENT		4072400507
			•		•	•					•	BLUE		4072400508
			•		•	•					•	RED		4072400509
			•		•	•					•	GREEN		4072400510
			•		•	•					•	YELLOW		4072400511
			•		•	•					•	WHITE		4072400512

6.a Rubber tools

CONE	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
  	50	NBR							•	•	•				Z7 21010
									•	•	•		GREY	Length 245 mm, GREY	80650900
									•	•	•		GREY	Length 500 mm, GREY	80691100
		CONDUCTIVE NBR							•	•	•	•			40000221
		STAINLESS STEEL + CONDUCTIVE NBR		•					•	•	•	• for EXA machines		Oilproof	4072400506
		SILICONE	•										TRANSPARENT		4072100111
			•										BLUE		4072100112
			•										RED		4072100113
			•										GREEN		4072100114
			•										YELLOW		4072100115
			•										WHITE		4072100116
		STAINLESS STEEL AISI 304 + SILICONE	•	Only dust, II 2D		•	•						TRANSPARENT		4072400513
			•			•	•						BLUE		4072400514
			•			•	•						RED		4072400515
			•			•	•						GREEN		4072400516
			•			•	•						YELLOW		4072400517
			•			•	•						WHITE		4072400518
	70	NBR			•	•	•	•	•	•	•				Z7 21009

The black nitrile rubber cones are the conductive model, while the red ones are standard. They are oil-resistant and therefore suitable for cleaning shavings and liquids from machine tools. The length varies from 200mm to a maximum of 500mm. The silicone version, available only with a 40mm diameter, is suitable for autoclaves. These cones can be connected both to junction fittings and curved fittings.

Coloured silicone versions are FDA approved and suitable for the food sector. They are all provided with metal connectors with the pushbutton already mounted.

This metal connection will keep the same diameter of the terminal tool.

Coloured tools have been tested to be used in zone 22 ATEX classified areas, so it means they can collect dust. The use of these accessories in zone 22 ATEX environment is allowed only if they are connected to an antistatic or dissipative flex hose by means of stainless steel metal parts, all provided by Nilfisk.

6.a Rubber tools

CONICAL TOOL D32	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	32	NBR			•					•		 GREY		81141101
		CONDUCTIVE NBR			•					•	•	 BLACK		81932600
		SILICONE	•		•	•	•					TRANSPARENT WHITE		81141103
	40	STAINLESS STEEL + CONDUCTIVE NBR		•	•					•	• for EXA machines	 BLACK	With reduction 40/32	4072400520
				•	•					•			With reduction 40/32 and with bristles on the top of the tool	4072400599
	The 240mm final cone is for use on the IVT1000 vacuum cleaner. Three versions are available: standard, anti-static and autoclave-safe (in silicone). They must always be used with the connecting tube (code 11882505) The certified and marked version is available both with bristles and without.													

50/20 CONICAL TOOL	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
 	40	ZINC-PLATED + CONDUCTIVE NBR			•			•	•	•	•		Supplied With 50/40 mm Reduction	Z7 22142
	50				•			•	•	•	•		Supplied with 50 mm Junction Fitting	Z7 22141
		STAINLESS STEEL + CONDUCTIVE NBR			•			•	•	•	•		Supplied with 50 mm stainless steel junction fitting	4072400416
		ANTISTATIC NBR			•			•	•	•	•		CURVED TIP (the fitting and the reduction are not included)	Z8 24046
		NBR			•			•	•	•			Optional spare part: straight shape (the fitting and the reduction are not included)	82167400
The 50/20 final cones are 300 mm long and are generally used to clean dust and thread-like residue.														

6.a Rubber tools

SILICONE CONICAL TOOL	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	FDA SILICONE	•			•	•						TRANSPARENT		4072100129
			•			•	•						 BLUE		4072100130
			•			•	•						 RED		4072100131
			•			•	•						 GREEN		4072100132
			•			•	•						 YELLOW		4072100133
			•			•	•						 WHITE		4072100134
		STAINLESS STEEL AISI304 + FDA SILICONE	•	Only dust, II 2D		•	•					• for EXA machines	TRANSPARENT		4072400534
			•			•	•						 BLUE		4072400535
			•			•	•						 RED		4072400536
			•			•	•						 GREEN		4072400537
			•			•	•						 YELLOW		4072400538
			•			•	•						 WHITE		4072400539
The silicone conical tool is available only in D40. This shape can be modified by cutting the tip of the nozzle thanks to predefined internal flanges. These final tools can be connected both to junction fittings and curved fittings.															

6.a Rubber tools

RUBBER NOZZLE	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
 	40	SILICONE	•			•	•						TRANSPARENT		4072100117
			•			•	•						 BLUE		4072100118
			•			•	•						 RED		4072100119
			•			•	•						 GREEN		4072100120
			•			•	•						 YELLOW		4072100121
			•			•	•						 WHITE		4072100122
		STAINLESS STEEL AISI 304 + SILICONE	•	• Only dust, II 2D		•	•					• for EXA machines	TRANSPARENT		4072400522
			•			•	•				 BLUE			4072400523	
			•			•	•				 RED			4072400524	
			•			•	•				 GREEN			4072400525	
			•			•	•				 YELLOW			4072400526	
			•			•	•				 WHITE			4072400527	
	50	NBR			•			•	•	•		 GREY	120 mm	Z7 21030	
		CONDUCTIVE NBR			•			•	•	•	•	 BLACK		Z7 21080	
		SILICONE	•			•	•						TRANSPARENT		4072100123
			•			•	•						 BLUE		4072100124
			•			•	•						 RED		4072100125
			•			•	•						 GREEN		4072100126
			•			•	•						 YELLOW		4072100127
			•			•	•						 WHITE		4072100128
		STAINLESS STEEL + CONDUCTIVE NBR	•	•	•	•	•	•	•	•	• for EXA machines	 BLACK	120 mm	4072400519	
				•	•			•	•	•		200 mm	4072400521		
		STAINLESS STEEL AISI 304 + SILICONE	•	• Only dust, II 2D		•	•					TRANSPARENT		4072400528	
						•	•				 BLUE		4072400529		

6.a Rubber tools

RUBBER NOZZLE	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
		STAINLESS STEEL AISI 304 + SILICONE		Only dust, II 2D		•	•					• for EXA machines	 RED		4072400530
						•	•						 GREEN		4072400531
						•	•						 YELLOW		4072400532
						•	•						 WHITE		4072400533
	50	NBR			•			•	•	•		 GREY	200 mm	80640500	
		CONDUCTIVE NBR			•			•	•	•		 BLACK		80640501	
		PVC			•			•	•	•		 BLACK		82167300	
	The rubber floor nozzle is ideal for removing shavings and dust, thanks to its toothed profile; it is available in a grey standard version and a black conductive version. The floor nozzle must be used with a 50/40mm reduction or a 50mm junction fitting. Alternatively, it can be used with a curved fitting and a 50/40mm reduction or a 50mm curved fitting. The PVC oilproof nozzle (25mm x 90mm) is a special nozzle in this group.														

CREVICE NOZZLES	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
 	32	STAINLESS STEEL AISI 304	•			•	•						For IVT1000, 250mm long	80552000	
	40	ZINC-PLATED			•			•	•	•			1 external flange	Z7 21027	
					•			•	•	•		Z7 22022			
		PVC			•			•	•	•			500mm	Z7 24014	
		STAINLESS STEEL AISI 304			•			•	•	•			1 external flange	40000213	
		STAINLESS STEEL AISI 316L	•			•	•					4072100148			
		STAINLESS STEEL AISI 316L + SILICONE	•			•	•					 BLUE	1 Internal flange and silicone ring	4072400388	
			•			•	•					 RED		4072400389	
			•			•	•					 GREEN		4072400390	
			•			•	•					 YELLOW		4072400391	
	•				•	•					 WHITE	4072400392			

6.a Rubber tools

CREVICE NOZZLES	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	STAINLESS STEEL AISI 304		•							• for EXA machines		EXA connection	4072100162
	50	ZINC-PLATED			•			•	•	•			1 external flange	Z7 21026
					•			•	•	•			1 internal flange	Z7 21074
					•			•	•	•			1 external flange	Z7 22021
					•			•	•	•				Z7 21075
		PVC			•			•	•	•			500mm	Z7 24013
		STAINLESS STEEL AISI 304			•			•	•	•			1 external flange	40000220
		STAINLESS STEEL AISI 316L	•			•	•							4072100149
		STAINLESS STEEL AISI 316L + SILICONE	•			•	•					 BLUE	Internal flange and silicone ring	4072400393
			•			•	•					 RED		4072400394
			•			•	•					 GREEN		4072400395
			•			•	•					 YELLOW		4072400396
			•			•	•					 WHITE		4072400397
		STAINLESS STEEL AISI 304		•	•			•	•	•	• for EXA machines		EXA connection	4072100163
	70	ZINC-PLATED			•			•	•	•			1 external flange	Z7 21028
		PVC			•			•	•	•			1000mm	Z7 24012
The crevice nozzles, made of metal and PVC are ideal for cleaning shavings, dust and liquids. In particular, the flat-tip crevice nozzles are the best tool for cleaning in corners, while the ones with perimeter brush effectively remove and clean dust. Metal flat-tip crevice nozzles are also available for special requirements, curved and with reductions. Coloured versions are available with an internal flange with a silicone coloured ring for the food sector.														

6.a Rubber tools

CREVICE NOZZLES WITH BRUSH	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	ZINC-PLATED			•			•	•	•			Steel perimeter brush	Z7 22024
					•			•	•	•			Nylon perimeter brush	Z7 22088
	50				•			•	•	•			Steel perimeter brush	Z7 22023
					•			•	•	•			Nylon perimeter brush	Z7 22089
Thre crevice nozzle with brush is ideal for cleaning sticky material that must be removed from the surface. Both steel and nylon brushes are available.														

CREVICE NOZZLES WITH HANDLES	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	70	ALUMINIUM			•			•	•	•				Z7 22169
	100				•			•	•	•				Z7 22190
Aluminium crevice nozzles with handles are recommended For more heavy-duty use.														

FLUIDIFYING NOZZLE	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	ZINC-PLATED			•			•	•	•				Z7 22053
	50				•			•	•	•				Z7 22054
		ALUMINIUM			•			•	•	•				ZA7210024
	70	ZINC-PLATED			•			•	•	•				Z7 22055
		ALUMINIUM			•			•	•	•				ZA7210026
	100				•			•	•	•				ZA7210019
The fluidifying tools are normally used when you have to clean a notable quantity of material, both scattered dust and heaps of dust. Thanks to the particular construction, with a double concentric tube, the fluidifying tool, with or without regulator, is very efficient during the suction phase.														

6.a Rubber tools

SCRAPER NOZZLES	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	ZINC-PLATED			•				•	•	•			Length 1000mm - Width 110mm	Z7 22033
		STAINLESS STEEL AISI 304			•				•	•	•				Z7 22277
				•	•			•	•	•	•	for EXA machines			4072100179
	50	ZINC-PLATED			•				•	•	•			Length 1000mm - Width 150mm	Z7 22034
		STAINLESS STEEL AISI 304			•				•	•	•				Z7 22278
				•	•			•	•	•	•	for EXA machines			4072100180
	70	ZINC-PLATED			•				•	•	•			Length 1000mm - Width 200mm	Z7 22090
	The scraper nozzles, available in various widths and one length (1000mm), are ideal for scraping and vacuuming floors. Also EXA version is available.														

ROUND BRUSHES	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE	
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	ZINC-PLATED			•			•	•	•				With nylon bristles, 1 internal flange and 1 quick-fit coupling with harmonic spring	Z7 22045
					•			•	•	•					Z7 22046
	50				•			•	•	•					Z7 22047
					•			•	•	•					Z7 22048
		NYLON BRISTLES												With nylon bristles, for round brush with D40	Z8 23005
														With nylon bristles, for round brush with D50	Z8 23006
		STEEL BRISTLES												with steel bristles, for round brushes with D40 and D50	Z8 23008
	Round brushes are generally used to clean dust. They can be connected directly to a hose using the relevant sleeve or can be connected to the extensions shown in chapter 4.b (in particular if used with quick-fit extensions, remember to always remove the harmonic spring from the fitting of the round brushes).														

6.a Rubber tools

CONDUCTIVE ROUND BRUSHES	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
  	40	Conductive PVC+nylon+brass										•	 BLACK	With black nylon bristles and brass bristles	4072400262
				•								• for EXA machines	 BLACK	With Stainless Steel EXA connector	4072400540
	50	Conductive PVC+nylon+brass										•	 BLACK	With black nylon bristles and brass bristles	4072400263
				•								• for EXA machines	 BLACK	With Stainless Steel EXA connector	4072400541
		Nylon+brass										•		SPARE PART: with nylon and brass bristles for the conductive version of the brush	4072400270
	Conductive round brushes are suitable for ATEX applications. These final tools can be connected both to junction fittings and curved fittings.														

6.a Rubber tools

COLOURED ROUND BRUSHES	Ø mm	MATERIAL	FEATURES		SECTORS							COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
   	38	ALUMINIUM			•						•		With polypropylene bristles, wood body with an aluminium fitting, 100mm diameter round brush	10989000
	50	NBR			•						•		With natural bristles	12422500
											•		Fitting spare part	80625000
	40	PVC + POLYPROPYLENE									•	■ BLACK	With black bristles made of polypropylene	4072200576
											•	■ RED	With red bristles made of polypropylene	4072200577
											•	■ GREEN	With green bristles made of polypropylene	4072200578
											•	■ BLUE	With blue bristles made of polypropylene	4072200579
											•	■ WHITE	With white bristles made of polypropylene	4072200580
											•	■ YELLOW	With yellow bristles made of polypropylene	4072200581
	50	PVC + POLYPROPYLENE									•	■ BLACK	With black bristles made of polypropylene	4072200570
											•	■ RED	With red bristles made of polypropylene	4072200571
											•	■ GREEN	With green bristles made of polypropylene	4072200572
											•	■ BLUE	With blue bristles made of polypropylene	4072200573
											•	■ WHITE	With white bristles made of polypropylene	4072200574
											•	■ YELLOW	With yellow bristles made of polypropylene	4072200575
		POLYPROPYLENE									•		With black bristles made of polypropylene	4072400264
											•	■ RED	With red bristles made of polypropylene	4072400265
											•	■ GREEN	With green bristles made of polypropylene	4072400266
											•	■ BLUE	With blue bristles made of polypropylene	4072400267
	40	FDA NBR + NYLON	•			•	•				•	■ BLUE	FDA approved material	4072400274
			•			•	•				•	■ RED		4072400275
			•			•	•				•	■ GREEN		4072400276
			•			•	•				•	■ YELLOW		4072400277
			•			•	•				•	■ WHITE		4072400278

6.a Rubber tools

COLOURED ROUND BRUSHES	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
   	40	FDA NBR + NYLON	•			•	•				•		 BLUE-BLUE	FDA approved material-blue connection and blue bristles	4072400606
			•			•	•				•		 RED-RED	FDA approved material-red connection and red bristles	4072400607
			•			•	•				•		 GREEN-GREEN	FDA approved material-green connection and green bristles	4072400608
			•			•	•				•		 YELLOW-YELLOW	FDA approved material-yellow connection and yellow bristles	4072400609
		STAINLESS STEEL + FDA NBR + NYLON		•		•	•				•	• for EXA machines	 BLUE	With Stainless Steel EXA connector	4072400542
				•		•	•				•		 RED		4072400543
				•		•	•				•		 GREEN		4072400544
				•		•	•				•		 YELLOW		4072400545
				•		•	•				•		 WHITE		4072400546
	50	FDA NBR + NYLON	•			•	•				•		 BLUE	FDA approved material	4072400279
			•			•	•				•		 RED		4072400280
			•			•	•				•		 GREEN		4072400281
			•			•	•				•		 YELLOW		4072400282
			•			•	•				•		 WHITE		4072400283
		STAINLESS STEEL + FDA NBR + NYLON		•		•	•				•	• for EXA machines	 BLUE	With Stainless Steel EXA connector	4072400547
				•		•	•				•		 RED		4072400548
				•		•	•				•		 GREEN		4072400549
				•		•	•				•		 YELLOW		4072400550
				•		•	•				•		 WHITE		4072400551
		NYLON BRISTLES	•			•	•				•		 WHITE	White bristles, suitable for all FDA round brushes	4082300058
These round brushes, all with a rubber structure (except for one model in wood and aluminium), are always used for removing and cleaning dust. The round brushes with 38mm coupling should be used together with the fitting with 40/38mm reduction (code 4072200390, see chap 3.b), while the brushes with 50mm coupling can be connected directly to the curved fittings shown in chapter 3.a. These two types of round brushes can also easily be connected to quick-fit extensions with harmonic spring (see chapter 4.b): via the fitting with 40/38mm reduction (code 4072200389) and via the 50mm coupling (code 4072200388), for round brushes with 38mm and 50mm couplings, respectively.															


6.a Rubber tools

COLOURED TRIANGULAR BRUSHES	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	FDA NBR + NYLON	•			•	•			•			 BLUE	FDA approved material	4072400284
			•			•	•			•			 RED		4072400285
			•			•	•			•			 GREEN		4072400286
			•			•	•			•			 YELLOW		4072400287
			•			•	•			•			 WHITE		4072400288
			•			•	•			•			 RED-RED	FDA approved material-red connection and red bristles	4072400602
	40	STAINLESS STEEL + FDA NBR + NYLON		•		•	•			•	• for EXA machines		 BLUE	With Stainless Steel EXA connector	4072400552
				•		•	•			•			 RED		4072400553
				•		•	•			•			 GREEN		4072400554
				•		•	•			•			 YELLOW		4072400555
				•		•	•			•			 WHITE		4072400556
	50	FDA NBR + NYLON	•			•	•			•			 BLUE	FDA approved material	4072400289
			•			•	•			•			 RED		4072400290
			•			•	•			•			 GREEN		4072400291
			•			•	•			•			 YELLOW		4072400292
			•			•	•			•			 WHITE		4072400293
	50	STAINLESS STEEL + FDA NBR + NYLON		•		•	•			•	• for EXA machines		 BLUE	With Stainless Steel EXA connector	4072400557
				•		•	•			•			 RED		4072400558
				•		•	•			•			 GREEN		4072400559
				•		•	•			•			 YELLOW		4072400560
				•		•	•			•			 WHITE		4072400561
		NYLON BRISTLES	•			•	•			•			 WHITE	White bristles, suitable for all FDA round brushes	4082300059
FDA triangular brushes are suitable for the Food sector to apply the colour coded program. These final tools can be connected both to junction fittings and curved fittings.															

6.a Rubber tools

COLOURED RECTANGULAR BRUSHES	Ø mm	MATERIAL	FEATURES		SECTORS								COLOR	NOTES	CODE
			AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL											
	40	FDA NBR + NYLON	•			•	•			•			 BLUE	FDA approved material	4072400294
			•			•	•			•			 RED		4072400295
			•			•	•			•			 GREEN		4072400296
			•			•	•			•			 YELLOW		4072400297
			•			•	•			•			 WHITE		4072400298
	40	STAINLESS STEEL + FDA NBR + NYLON		•		•	•			•			 BLUE	With Stainless Steel EXA connector	4072400562
				•		•	•			•			 RED		4072400563
				•		•	•			•		•	 GREEN		4072400564
				•		•	•			•			 YELLOW		4072400565
				•		•	•			•			 WHITE		4072400566
	50	FDA NBR + NYLON	•			•	•			•			 BLUE	FDA approved material	4072400299
			•			•	•			•			 RED		4072400300
			•			•	•			•			 GREEN		4072400301
			•			•	•			•			 YELLOW		4072400302
			•			•	•			•			WHITE		4072400303
	50	STAINLESS STEEL + FDA NBR + NYLON		•		•	•			•			 BLUE	With Stainless Steel EXA connector	4072400567
				•		•	•			•			 RED		4072400568
				•		•	•			•		•	 GREEN		4072400569
				•		•	•			•			 YELLOW		4072400570
				•		•	•			•			WHITE		4072400571
		NYLON BRISTLES	•			•	•			•			 WHITE	White bristles, suitable for all FDA round brushes	4082300060
FDA rectangular brushes are suitable for the Food sector to apply the colour coded program. These final tools can be connected both to junction fittings and curved fittings.															

6.b Examples: **final tools**



E

Ø 50 mm
Curved fitting
Z7 21034




I

Ø 50 mm
Cone
Z7 21010




K

Ø 50 mm
Rubber nozzle
Z7 21080



C

Ø 40 mm
3-meter Air Hose with sleeves
Z7 22049




I

Ø 40 mm
Conical tool
Z7 22142

6.b Examples: final tools

C




Ø 50 mm
3-meter Polyurethane Hose with sleeves
Z7 22298

A




Ø 50 mm
Junction Fitting
Z7 21002

I



Ø 50 mm
Rubber nozzle
4072100124

C




Ø 40 mm
3-meter conductive Flex Hose with sleeves
Z7 22150

K




Ø 40 mm
Scraper nozzle
Z7 22033

C



Ø 50 mm
3-meter conductive Flex Hose with sleeves
Z7 22375


G



Ø 50 mm
Curved flat-tip crevice nozzle
Z7 21075

6.b Examples: final tools


C



Ø 70 mm

3-meter Polyurethane Hose with sleeves
Z7 22299


K



Ø 70 mm

Round crevice nozzle with handles
Z7 22169

K



Ø 70 mm

Fluidifying vulk nozzle with regulator
ZA7210026

D



Ø 40 mm

Quick-fit extensions with harmonic spring
Z7 22386

A



Ø 40/38 mm

Extension fitting
with reduction
4072200389

I



Ø 38 mm

Round brush
10950202

6.b Examples: **final tools**

D




Ø 40 mm

Quick-fit extensions with harmonic spring

Z7 22386

J




Ø 40 mm

Round brush

Z7 22045

C




Ø 50 mm

Air Hose by meter

Z7 22062

H




Ø 50 mm

Round brush

Z7 22047

6.b Examples: final tools

F




Ø 40 mm
EXA bent fitting
4072100160

K



Ø 40 mm
Silicone cone D40 blue ATEX complete
4072400508

J



Ø 50 mm
Conductive nozzle D50 120mm ATEX complete - suction point 120 mm
4072400519

K




Ø 32 mm
Conductive nozzle D32 240mm length ATEX complete + Stainless Steel reduction D40/32
4072400599

J



Ø 40 mm
Silicone conical tool FDA red D40/20 ATEX complete
4072400544

6.b Examples: final tools



Ø 40 mm
EXA bent fitting
4072100160



Ø 40 mm
Round brush FDA green D40 ATEX complete
4072400544




Ø 40 mm
EXA extension
4072400658



Ø 40 mm
Round brush FDA blue D40 ATEX complete
4072400542



Ø 40 mm
3-meter Flex Conductive Hose
4072400451



Ø 40 mm
Rectangular brush D40 ATEX complete red
4072400542

Accessories Kit

A wide range of kits is available: from sets of accessories for general cleaning, to kits for special applications (ex. cleanrooms), to groups of accessories for typical industrial applications and series of accessories for cleaning machinery in general.



GENERAL CLEANING KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS								CODE
				OILPROOF	CONDUCTIVE (*)	ANTISTATIC (**)	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	· Zinc-plated reduction Ø 50/40 · 3m Flex hose with sleeves · Chromed handgrip · Wheeled floor nozzle for dust and liquids (width 400mm) · Rubber cone · Round brush with Nylon bristles (80mm) · Zinc-plated flat-tip crevice nozzle (length 500mm) · Zinc-plated junction fitting														•	Z7 24145
	50	3	· Zinc-plated reduction Ø 70/50 · 3m Flex hose with sleeves · Chromed handgrip · Wheeled floor nozzle for dust and liquids (width 500mm) · Rubber cone · Round brush with Nylon bristles (100mm) · Zinc-plated flat-tip crevice nozzle (length 500mm) · Zinc-plated junction fitting														•	Z7 24146
The accessories kit for general cleaning is a set of components suitable for light applications. Thanks to the numerous elements (handgrip, wheeled floor nozzle, cone, flat-tip crevice nozzle, etc.) it is extremely versatile. It is available in two sizes: 40mm and 50mm diameter.																		

INDUSTRIAL CLEANING KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS							CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL								
	40	3	· Zinc-plated reduction Ø 50/40 · 3m Polyurethane hose with sleeves · Chromed handgrip · Wheeled floor nozzle for dust and liquids (width 400mm) · Rubber cone · Round brush with Nylon bristles (80mm) · Zinc-plated flat-tip crevice nozzle (length 500mm) · Zinc-plated junction fitting			•				•			•	•	•		Z7 24150
	50	3	· Zinc-plated reduction Ø 70/50 · 3m Polyurethane hose with sleeves · Chromed handgrip · Wheeled floor nozzle for dust and liquids (width 500mm) · Rubber cone · Round brush with Nylon bristles (100mm) · Zinc-plated flat-tip crevice nozzle (length 500mm) · Zinc-plated junction fitting			•				•			•	•	•		Z7 24151
	70	5	· Zinc-plated reduction Ø 100/70 · 5m Polyurethane hose with sleeves · Chromed handgrip · Wheeled floor nozzle for dust and liquids D70 (width 500mm) · Zinc-plated junction fitting · Rubber cone			•				•			•	•	•		4072400247
The industrial cleaning accessories kit is ideal for cleaning spacious areas. Consisting of a 3 meter polyurethane hose, and a complete set of single accessories, this kit lets you clean areas quickly and effectively. The kit in D70 includes the hose in 5m length. The hose must be connected properly if needed.																	

CLEANING MACHINERY KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS							CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL								
	40	3	· Zinc-plated reduction Ø 50/40 · 3m Polyurethane hose with sleeves · Zinc-plated junction fitting · Conical tool · Rubber cone			•				•			•	•	•		Z7 24155
	50	3	· Zinc-plated reduction Ø 70/50 · 3m Polyurethane hose with sleeves · Zinc-plated junction fitting · Conical tool · Rubber cone · Rubber sucker			•				•			•	•	•		Z7 24156
	70	5	· Zinc-plated reduction Ø 100/70 · 5m Polyurethane hose with sleeves · Zinc-plated junction fitting · Conical tool · Zinc-plated flat lance			•				•			•	•	•		4072400248
The kit for cleaning machinery is a set of accessories specifically designed for cleaning dust and residues in general from machinery used during the phases of production and/or other processes. Thanks to the specific components, such as the rubber cone, cleaning is particularly effective. Also in this case there are three available sizes: 40mm, 50mm e 70mm diameter. The hose must be connected properly if needed.																	

FLOORS AND MACHINERY OILPROOF KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS							CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL								
	40	3	· Zinc-plated reduction Ø 50/40 · 3m rubber hose with sleeves · Zinc-plated junction fitting · Rubber cone · Chromed handgrip · Wheeled floor nozzle for dust and liquids (width 400mm)	•	•					•			•	•	•		4072400194
	50	3	· Zinc-plated reduction Ø 70/50 · 3m rubber hose with sleeves · Zinc-plated junction fitting · Rubber cone · Chromed handgrip · Wheeled floor nozzle for dust and liquids (width 500mm)	•	•					•			•	•	•		4072400195
	70	5	· Zinc-plated reduction Ø 100/70 · 5m rubber hose with sleeves · Zinc-plated junction fitting · Rubber cone · Chromed handgrip · Wheeled floor nozzle for dust and liquids (width 500mm)	•	•					•			•	•	•		4072400249
The oilproof accessories KITS, for both floors and machinery, are suitable for treating all surfaces where oils have to be sucked up. Consisting of oil-resistant rubber accessories, these kits are available in two sizes: 40mm, 50mm and 70mm diameter.																	

PHARMA ACCESSORIES KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS								CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	· AISI 316L reduction Ø 50/40 · 3m antistatic hose with sleeves · AISI 316L bent connection · AISI 316L flat lance · AISI 316L handgrip · Mobile nozzle + silicone · Silicone cone			•			•		•	•						4072200612
	50	3	· AISI 316L connection tube Ø 50 · 3m antistatic hose with sleeves · AISI 316L bent connection · AISI 316L flat lance · AISI 316L handgrip · Mobile nozzle + silicone · Silicone cone			•			•		•	•						4072200613
	40	3	· AISI 316L reduction Ø 50/40 · 3m silicone hose with sleeves · AISI 316L bent connection · AISI 316L flat lance · AISI 316L handgrip · Mobile nozzle + silicone · Silicone cone					•	•		•	•						4072200614
	50	3	· AISI 316L connection tube Ø 50 · 3m silicone hose with sleeves · AISI 316L bent connection · AISI 316L flat lance · AISI 316L handgrip · Mobile nozzle + silicone · Silicone cone					•	•		•	•						4072200615
Two different kits have been developed according to the main needs in the pharmaceutical production companies. The difference is the type of hose: the standard kit includes the antistatic transparent hose, while the premium kit includes the new silicone hose.																		

IVT1000 KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS								CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	32	3	· 3m plastic hose with sleeves · Stainless steel extension/handgrip (2 pieces) · Standard nozzle (width 300mm) · Stainless steel connecting tube (length 250mm) · Rubber cone · Stainless steel flat-tip crevice nozzle (length 250mm) · Metal hose clamp (2 pieces)									•	•		•			80551100
			· 3m antistatic plastic hose with sleeves · Stainless steel extension/handgrip (2 pieces) · Antistatic nozzle (width 300mm) · Stainless steel connecting tube (length 250mm) · Conductive conical tool · Stainless steel flat-tip crevice nozzle (length 250mm) · Metal hose clamp (2 pieces)			•						•	•		•			80551200
			· 3m silicone hose with sleeves · Stainless steel extension/handgrip (2 pieces) · Nozzle for autoclaves (width 300mm) · Stainless steel connecting tube (length 250mm) · Silicone cone · Stainless steel flat-tip crevice nozzle (length 250mm) · Metal hose clamp (2 pieces)					•				•	•		•			
These three accessories kits are only for the IVT1000 vacuum cleaner. All three are only available with a 32mm diameter. While the standard set is indicated for light applications, the antistatic kit is ideal where antistatic applications are required; the autoclave kit is an optimal solution for all applications where the accessories have to be sterilized. The metal accessories are made of AISI316 stainless steel.																		

ALIMENTARY KIT FLOOR	Ø mm	LENGTH meters	COMPOSITION	FEATURES							SECTORS								CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCCLAVABLE	CERTIFIED THIRD PARTY APPROVAL										
	40	3	· Stainless steel reduction Ø 50/40 · 3m rubber hose for food · Stainless steel handgrip · Stainless steel wheeled floor nozzle for dust and liquids (width 400mm)	•								•	•						4072400210
	50	3	· Stainless steel hose fitting Ø 50 · 3m rubber hose for food · Stainless steel handgrip · Stainless steel wheeled floor nozzle for dust and liquids (width 400mm)	•								•	•						4072400209
	40	3	· Stainless steel reduction Ø 50/40 · 3m rubber hose for food · Stainless steel junction fitting · Flat lance · Silicone cone	•								•	•						4072400206
	50	3	· Stainless steel reduction Ø 50/40 · 3m rubber hose for food · Stainless steel junction fitting · Flat lance · Silicone cone · Silicone nozzle	•								•	•						4072400205
The alimentary kit includes an FDA hose and there are two versions for floor cleaning and machinery cleaning.																			

OVENS KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS							CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCCLAVABLE	CERTIFIED THIRD PARTY APPROVAL								
	40	3	3m flexible steel hose with zinc-plated reduction and fitting - Al 1m extension (3 pieces) with quick-fit coupling - Wheeled nozzle for cleaning ovens - Sliding PTFE sleeve				•				•			•			Z7 24193
	50	3	3m flexible steel hose with zinc-plated reduction and fitting - Al 1m extension (3 pieces) with quick-fit coupling - Wheeled nozzle for cleaning ovens - Sliding PTFE sleeve				•				•			•			Z7 24192
	40	3	- High temperature flexible hose (3 meters + metal ties) with zinc-plated reduction and fitting - Aluminum 1 m extension (3 pieces) with quick-fit coupling - Wheeled nozzle for oven cleaning - Sliding PTFE sleeve				•				•			•			4072200616
	50	3	3 m steel hose with zinc-plated reduction and fitting - Aluminum 1 m extension (3 pieces) with quick-fit coupling - Wheeled nozzle for cleaning ovens - Sliding PTFE sleeve				•				•			•			4072200617
The oven cleaning kit is a specific set of accessories designed for cleaning inside ovens. Consisting of a 3 meter steel hose, with sleeve (silicone) and all the fittings and reductions necessary, three 1m extensions with a sliding PTFE sleeve and a wheeled nozzle with two silicone lips, this set is very practical and effective, also thanks to the connecting system (with harmonic spring) and the reduced weight. There are two sizes available: 40mm and 50mm diameter. The kit with the flexible hose includes the hose made up with glass fiber and silicone reinforced tissue with galvanized steel spiral and its metal ties.																	

ATEX KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS							CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL								
	40	3	3m Flex conductive Hose - Conductive sleeve (2 pieces D38) - Stainless steel handgrip - Stainless steel wheeled floor nozzle for dust and liquids (width 400mm) - Stainless steel curved fitting - Conductive cone - Stainless steel flat-tip crevice nozzle		•					•		•	•	•		•	Z7 24185
	38/40	3	3m Flex conductive Hose - Conductive sleeve (2 pieces D38/40) - Stainless steel handgrip - Stainless steel wheeled floor nozzle for dust and liquids (width 400mm) - Stainless steel curved fitting - Conductive cone - Stainless steel flat-tip crevice nozzle		•					•		•	•	•		•	4072400246
	50	3	3m Flex conductive Hose - Conductive sleeve (2 pieces) - Stainless steel handgrip - Stainless steel wheeled floor nozzle for dust and liquids (width 400mm) - Stainless steel curved fitting - Conductive cone - Stainless steel flat-tip crevice nozzle		•					•		•	•	•		•	Z7 24182
	40	3	3m Flex conductive Hose - Conductive sleeve (2 pieces D38) - Stainless steel handgrip - Stainless steel wheeled floor nozzle for dust and liquids (width 400mm)		•					•		•	•	•		•	Z7 24186
	50	3	3m Flex conductive Hose - Conductive sleeve (2 pieces) - Stainless steel handgrip - Stainless steel wheeled floor nozzle for dust and liquids (width 400mm)		•					•		•	•	•		•	Z7 24183

ATEX KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS								CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	3	· 3m Flex conductive Hose · Conductive sleeve (2 pieces D38) · Stainless steel curved fitting · Conductive cone · Stainless steel flat-tip crevice nozzle		•						•		•	•	•		•	Z7 24187
	50	3	· 3m Flex conductive Hose · Conductive sleeve (2 pieces) · Stainless steel curved fitting · Conductive cone · Stainless steel flat-tip crevice nozzle		•						•		•	•	•		•	Z7 24184
	40	3	· 3m Flex conductive Hose · Conductive sleeve (2 pieces D38) · Conductive cone · Stainless steel flat-tip crevice nozzle		•						•		•	•	•		•	Z7 24175
The ATEX accessories kits, including the kit for the 15ATEX vacuum cleaner, are an optimal solution when conductivity is obligatory. Available in three versions, from the complete version for cleaning both floors and machinery, to the version for cleaning machinery, or the set for cleaning floors, these accessories kits consist of conductive or antistatic elements. Each kit is available in two different sizes: 40mm and 50mm diameter.																		

ANTISHOCK KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS								CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	5	· chromed reduction (the reduction 50/40 for the kit D40, and the reduction 70/50 for the kit D50) · 5 m flex conductive hose · 2 conductive sleeves · Chromed handgrip			•							•				4072200653	
	50		· Wheeled anti-shock floor nozzle for dust (width 400mm) with silicone lips · Zinc plated curved fitting · Antistatic round brush · Zinc plated flat lance · Conductive cone			•							•				4072200652	
The new anti-shock version has been implemented to be used in the B&C sector in order to dissipate any static charges caused by the passage of dust. It includes a conductive hose, a conductive cone, an antistatic round brush and a specific anti-shok nozzle with silicone lips.																		


EXA KIT	Ø mm	LENGTH meters	COMPOSITION	FEATURES						SECTORS								CODE
				OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	5	ATEX Accessories Kit (complete) · Conductive Hose 5m, · Handgrip, · Curved Connection, · Mobile Sucker, · Conductive Cone, · Flat Lance, · Antistatic Round Brush		•				•	•		•	•	•	• for EXA machines	4072200662		
	50				•				•	•		•	•	•		4072200663		
	40	5	ATEX Antistatic Accessories Kit (complete) · Antistatic Hose 5m, · Handgrip, · Curved Connection, · Mobile Sucker, · Conductive Cone, · Flat Lance, · Antistatic Round Brush			•			•	•		•	•	•		4072200666		
	50					•			•	•		•	•	•		4072200667		
	40	5	Antistatic Accessories Kit for floor cleaning · Antistatic Hose 5m, · Handgrip, · Mobile Sucker			•			•	•		•	•	•		• for EXA machines	4072200668	
	50					•			•	•		•	•	•			4072200669	
	40	5	Antistatic Accessories Kit for machines cleaning · Antistatic Hose 5m, · Curved Connection, · Conductive Cone, · Flat Lance, · Antistatic Round Brush			•			•	•		•	•	•	4072200670			
	50					•			•	•		•	•	•	4072200671			
The EXA accessories kit includes certified accessories suitable for EXA machines. It is available in 2 versions for cleaning both floors and machinery. All items include the PIN connection.																		

The EXA accessories kit includes certified accessories suitable for EXA machines. It is available in 2 versions for cleaning both floors and machinery. All items include the PIN connection.


OVERHEAD CLEANING KIT	Ø mm	COMPOSITION	FEATURES						SECTORS								CODE
			OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	40	· Adapter for the hose · 4 Carbon fiber poles (6 meters) · 2 Round brushes of different diameters · Conductive flat lance · 2 Curved connectors		•				•	•	•	•	•				•	4072400651
	The new carbon fiber kit is suitable for overhead cleaning. It doesn't include the hose, so it can be connected to standard hoses with sleeves. It can be used with EXA machines thanks to the connection hoses. (see chapter 2.a Hoses- connection EXA hoses).																

CONVERSION KIT	Ø mm	COMPOSITION	FEATURES						SECTORS								CODE
			OILPROOF	CONDUCTIVE	ANTISTATIC	HIGH TEMPERATURE	AUTOCLAVABLE	CERTIFIED THIRD PARTY APPROVAL									
	50	Conversion kit for grey line machines							•			•	•	•	• for EXA machines	4089100928	
	70								•			•	•	•		4089100929	
	100								•			•	•	•		4089100930	
	50	Conversion kit for VHW series							•			•	•	•		4089100981	
	70								•			•	•	•		4089100982	
The conversion kit has been developed to allow the usage of EXA certified accessories also on machines already on the field. They are available for both the Grey line and also the White line.																	

Notes



Notes



Nilfisk S.p.A. a socio unico

Via Porrettana, 1991 - 41059 Zocca, (Modena) - Italy

Tel. +39 059 9730000 - Fax +39 059 9730065

industrial-vacuum@nilfisk.com

www.nilfisk.com

